



eneo Center

Article number: 217368

Remote Software IER-25xx, IER-28xx, IER-38xx, MSR-24xx, MSR-25xx, MER-Serie

Software support UHD (3840x2160) resolution	Hotspot window for event monitoring
Live screen (Max. 4 monitors @ 64 tabs)	Remote access to recorder and cameras
User-defined display layouts	Playback and backup function
Live, Playback, Status, and Event Monitoring	Drag & drop control via mouse, PTZ control
Multilingual user interface	Support Dewarping Funktion (ISD-55_59)
Supports eneo IP cameras (Live & PTZ)	Compatible with Windows and Mac OS

Specifications

Playback format	H.264, H.265
Multi monitor operation	yes
Alarm management	yes
Alarm administration	yes
e-PTZ support	yes
Site maps	yes
Operation system	Windows 7, Windows 10, Mac OSX (10.11 Minimum)
Hardware recommendation (RAM)	8 GB
Series	eneo IE-Series, Safe & Easy
Control units (external)	mouse, keyboard
Licensing method	unlimited
RAM	Internal memory 8GB or more
Software Categorie	Video Management
Supported video sources	IER-25xx, IER-28xx, IER-38xx, MSR-24xx, IEM-38xx, DLR-21xx (Type A), MPR-32xx (Type A), MPR-22xx (Type A), PNR-53xx (Type A), MER-24xx (Type C), MER-34xx (Type C), MER-38xx (Type C), eneo IP Cameras (Live)
Managable video sources max.	256
Application	single user solution

Languages (client)	English, German, French, Italian, Korean, Chinese

www.eneo-security.com

More product information

The integration of DLR, MER, MPR and PNR recorders is limited to a maximum of 16 sources, Support for 4-eye-principle

Supported Video Sources:
IER-25xx Recorder Series,
IER-28xx Recorder Series,
IER-38xx Recorder Series,
MSR-24xx Recorder Series,
IEM-38xx Matrix,
MER-28xx, MER-38xx, MER-24xx, MER-34xx Series (Live, Playback, PTZ, Export)
DLR-21xx Recorder Series (Live & Playback)
MPR Recorder Series (Live & Playback)
PNR-53xx Recorder Series (Live & Playback)
eneo IP Cameras (Live)

