



F03Z2.6DC-NFSHR

Article-No.: 43274

F1.0/3-8mm DC Lens, Varifocal, No Focus Shift, High Resolution, 1/3" CS Mount

Mainfeatures

Suitable for 1/3" and 1/4" day&night cameras High resolution realizing 650 TV lines Minimized chromatic abberation Aspherical lens elements CS mount Variable focal length/Fast maximum aperture (F1.0) Clear images without colour smear No-focus-shift between visible and near IR light LD (Low Dispersion) glass Without built-in auto iris amplifier

Specifications

| Lens type | varifocal | |
|-------------------------------|---|--|
| Day/Night | yes | |
| Megapixel | no | |
| Aspherical technology | yes | |
| Nominal format size | 1/3" | |
| Flange focal length | 12.5mm | |
| Mount | CS | |
| Focal length | 3 mm - 8 mm | |
| Horizontal angle of view | 92,5° - 35,4° | |
| MOD (Minimum object distance) | 0,3 m | |
| Aperture range (F) | F1.0~F360 | |
| Iris control | DC | |
| Focus constant range | +0.05mm at f4,0; +0.015mm at f5.5mm; +0.05mm at f8mm | |
| | (Focus deviation at switch-over to IR light at 850nm) | |
| Resolution | 650 TV lines | |
| Screw-in depth | 4.0mm | |
| Filter screw size | not available | |
| Cable length | approx. 20cm | |


1




Specifications (continued)

| 4-pin plug | Standard |
|-------------------------------|---------------|
| Temperature range (operation) | -20°C ~ +60°C |
| Length | 54,4 mm |
| Diameter | 43,2 mm |
| Radius | 32 mm |
| Dimensions (HxWxD) | see drawing |
| Colour | Antracite |
| Weight | 75g |

Technical Drawing





Maße/Dimensions: mm



| Your partner for eneo products: | | |
|---------------------------------|--|--|
| | | |
| | | |
| | | |
| | | |