



HDR-4082AH1.0

Article-No.: 203354

Digital Video Recorder,
Hybrid, 2x HD-SDI, 8x D1,
H.264, 1TB, 1920x1080

Mainfeatures

Pentaplex operation
Hybrid, 2x HD-SDI, 8x Analogue BNC inputs
Video output resolution: 1920x1080
Network: 10/100/1000 Base-T Ethernet port
Storage capacity: 8TB (4 HDDs max.)
Browser & 3G mobile access

H.264 video compression standard
Recording speed: 50fps @ 1920x1080, 200fps @ D1
HDMI and VGA outputs
Archiving via USB 2.0
Digital zoom during live & playback
IR remote control and mouse control



Specifications

Series	eneo HDcctv
Operation mode	Pentaplex, Hybrid
Operation Mode	live, record, playback, backup, network
Channels total	10
Video inputs (amount)	10
Video inputs	2x HD-SDI (BNC) SMPTE 292M
IP channels	-
Main video outputs	HDMI, VGA
Spot monitor	4x composite (CVBS)
Audio inputs	10
Audio inputs	RCA
Audio output	1x line out (1Vpp), Cinch connector
Alarm inputs	10
Motion detector	Free selectable areas
Covert camera mode	available
Alarm triggers	disk error, motion detection, video loss, contact

Specifications (continued)

Alarm outputs	Relay contact (NO/NC)
Alarm notification	e-mail notification, alarm output
Event logs	yes
Max. recording resolution	1920x1080p
Compression standard	H.264
Max. recording rate	250 fps
Recording speed	50 fps @ 1920x1080, , 50fps @ 1280x720, 50fps @ 640x360, 200 fps @ 704 x 576, 200 fps @ 704 x 288, 200 fps @ 352 x 288
Number of HDD (internal)	max. 4 x SATA
Harddisk capacity (internal)	1 TB
Max. harddisk capacity (internal)	8 GB
Recording	permanent, timer, movement, manual, contact
Digital signature	watermark
Pre-alarm recording	up to 20min.
Post-alarm recording	up to 60sec.
Playback	full screen, , 10 channel split
Patrol mode	yes
Search function	event, date/time, system log, archive
Integrated writer	no
Secondary Storage	to USB Stick
Control units (external)	mouse, remote control
Remote access	Microsoft Internet Explorer
Mobile access	iPhone, Android OS, Blackberry
Time synchronization	NTP
Menu languages	German, English, French, Spanish, Italian, Greek, Russian, Turkish, Finnish, Thai, Croatian, Polish, Brazilian, Japanese, Korean, Chinese, Danish, Czech, farsi
Network	10/100/1000 Base-Tx, RJ45
Network protocols	HTTP, DDNS, NTP, SMTP, RTP, RTCP, DHCP
Transmission rate (Network)	250 Pict./sec.
Firmware update	USB Flash drive, via network
Interfaces external storage	eSATA
Serial interfaces	RS-485, RS-232
Serial interfaces protocols	Pelco D, Pelco P
Text insertion interface	no
Password protection	administrator & users
Operation system	Linux
Power consumption	70W
Temperature range (operation)	0°C ~ +40°C
Housing	Metal/Plastic
Colour	antracite / black
Dimensions (HxWxD)	98x432x430
Weight	7.4kg
Parts supplied	manual, IR remote controller, HDD assembly-kit, mouse, power cord, remote viewer software
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	HDD-2000SATA	Hard Disk Drive 2TB, SATA for eneo BLR, DLR, DMR,HDR Series
	KBD-2	System Keyboard with 3-Axis Joystick and Jog Shuttle, 12VDC

Your partner for eneo products:

