



IAM-5SE1004MUB

Article number: 219379

Switch, unmanaged, 120W, 4xPoE 1x RJ45, 1x SFP 100Mbps, Industrial Design, -40°C~+75°C

Ethernet PoE Switch, DIN Rail

Uplink ports 1xRJ45, 1xSFP

4x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -40° C ~ +75° C

Specifications

Features:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no

Network:	
Ethernet Standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	0,9 Mpps
Internal switching capacity (Gbit/s)	1,5 Gbps
VLAN	yes

Interfaces / Inputs / Outputs:	
Ethernet interface	10Base-T, 100Base-TX
Ports	4x 10/100Base-TX, 1x 100 SFP, 1x 10/100Base-TX
Optical connection	SFP Port

General:	
Dimensions (HxWxD)	46x110x159mm
19" Rack mountable	no
Number PoE ports	4
Model	DIN rail module
Type	Layer2 switch
Weight	530g
Blower	no
Management	no
Mounting	DIN rail, wall mount
PoE Power	120 W
Power over Ethernet	IEEE 802.3at
Supply voltage	40-57 VDC
Temperature range (operation)	-40°C ~ +75°C

Scope of delivery:	
Parts supplied	manual, power cord, Mounting Bracket, PSU

Notes:	
Remarks	Specification external power supply: 100-240VAC, 150W, 30x70x150mm, -30°~+70°, CCTV mode: transmission of 10Mbps @ 250m, CCTV mode, PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m
Application	indoor

Product recommendations



SFP-0850MM10 | SKU: 216567

