



IPC-52A0003M0B

Article number: 219027

1/2,8" Network Camera, 1920x1080, Day&Night, AF Zoom, WDR, 3,2-9 mm, Indoor

1/2,8" Sony STARVIS CMOS

Resolution max. 1920x1080 (Full HD)

Optical 3x Auto Focus Zoom, 16x Digital

3~9 mm day&night zoom lens, IR cut filter

VerticalView 90°/270° mode only H.264, HTML5 Playback

DOL-WDR by triple scan images at 30/25fps

VCA Video Analytic, ONVIF Event Mapping

Cross Web Browsing (IE, Safari, Firefox, Chrome)

Responsive Web Design, Zero configuration

Triple Streaming: 2x H.264, 1x MJPEG

Slot for Micro SD card

ONVIF conformity, PoE IEEE802.af

Specifications

Camera:		Features:	
Camera type	Zoom Camera	Audio	2 Way Audio
Sensor size	1/2.8"	Audio support	yes
Resolution standard	HD 1080p	Password protection	yes
Imager	CMOS, Sony STARVIS, Sensor IMX290	e-PTZ support	yes
System	True Day&Night	Internal storage	microSDHC card, microSDXC card
Sensitivity	0,1 Lux, at F1.6, 40IRE	Menu languages	English, German, French, Polish, Finnish
Low speed shutter	yes, automatic	Privacy zones masking	Areas-ON/OFF switchable
Manual electronic shutter (MES)	1/25~1/60000sec.	Remote configuration	web browser
Automatic electronic shutter (ESC)	1/25 ~ 1/60.000sec.	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Wide Dynamic Range (WDR)	DOL-WDR 120dB	User interface	Type A (orange / grey)
Flickerless function	yes	Mirror function	mirror, flip
Backlight compensation	BLC, HLC	Digital Noise Reduction (DNR)	yes
Day/Night switching	extern (Sensor), day, night, auto, night-color mode	Network:	
IR cut filter	switchable	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
White balance	automatic, ATW, manual	Interfaces / Inputs / Outputs:	
Signal-to-noise ratio	50dB	Video outputs	composite (CVBS)
Video:		External connections	RJ-45, audio input/output, alarm in/output, voltage input, micro SD card slot
Resolution	1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Ethernet interface	10Base-T, 100Base-TX
Resolution max.	1920x1080	Alarm inputs	1
Resolution max. [#1]	VerticalView 90°/270°, 4:3, 16:9	Alarm outputs	1
Stream types	2x H.264, 1x MJPEG multiple	Serial interfaces	Ethernet
Image transmission rate max.	30 fps	General:	
Compression standard	H.264, MJPEG	Series	eneo KN-Series, eneo Candid Box
Lens:		Dimensions (HxWxD)	72x74x125mm
Lens type	auto focus zoom	Mount	1/4" UNC, 2x M6
Zoom factor	2,8x	Illumination	no
Focal length	3,2 - 9 mm	Colour (housing)	Pantone Cool Gray 1C
Digital zoom	12x	Housing	indoor
MOD (Minimum object distance)	0,5 m	Housing material	aluminium
Iris control	DC	Weight	450g
Vertical angle of view	55 - 20 °	Power consumption	6.5W
Horizontal angle of view	104 - 35 °	Blower	no
DORI:		ONVIF	ONVIF Profile S
Detection (25 px/m)	45 - 120 m	Power over Ethernet	IEEE 802.3af
Observation (62 px/m)	18 - 49 m	SDK	upon request
Recognition (125 px/m)	8,4 - 24 m	Supply voltage	12VDC, 24VAC, PoE
Identification (250 px/m)	3,9 - 7 m	Temperature range (operation)	-10°C ~ +50°C
Features:		Text display	supplied
Multicast compliant	yes	Scope of delivery:	
Motion detector	yes	Parts supplied	manual
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, Defog		
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out		

Related Products



PS12DC-11 | SKU: 218653



WD-30 | SKU: 219504

More product information

Preset Zoom (4 adjustable positions)

Product recommendations



IAR-7SE1024MMA | SKU: 214460



IAM-5SE1008MUA | SKU: 214459



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472




IAR-7SG1008MMA | SKU: 216473



IAR-7SG1016MMA | SKU: 216474



IAR-7SG1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

