

## MCAB-1

Article-No.: 87404

Camera/PT Head Connecting  
Cable, for Video, Power, RS  
Control, Network, 1m, 100m max

### Mainfeatures


For camera housing and P/T head connection  
Data cable S/UTP (patch) 4x2xAWG26/7-PVC  
Power supply approved for 230VAC

Very flexible cable  
Power supply: 3x 0.75mm<sup>2</sup>  
Video coax cable 0.42L/2.54z

### Specifications

Colour	black
Outside dimensions	Total diameter: 10.5 +/-0.3mm (PVC)
Supply voltage	Wire cores: Cu, 1.15mm. Wire isolation: PVC, 2.2mm diam. No. of wires/colour: 3/black, blue, gn-ye.
Signal connection	S/UTP (Patch) 4x2xAWG26/7-PVC for data and/or control signal transmission. Wires: Cu, 0.48mm. Wire isolating: Cell PE 1.0mm. No. of wires: 8. 2 wires drilled each, 4 pairs drilled. First shield: Cu, soldered. Second shield: PVC. Total diameter: approx. 5.7mm.
Video signal transmission	Coax cable: Cu, 0.42mm. Isolation: PE 2.54mm. Shield: Cu, soldered
Plug	A BNC plug can be assembled on the coax wire (RG137, see accessories)

## Optional Accessories

Image	Artikel-Nr. / Typ	Description
	B/0.42	BNC Crimp Plug for Cable #87404 (\"0,42\")

Your partner for eneo products:

