

NLS-1401

Home | Security | IP Server/Decoder | Servers

NLS-1401
Network Video Server, 1-channel, H.264, MPEG-4,
MJPEG, 12VDC/24VAC, PoE, ONVIF

Art-Nr. 93104



ONVIF



Main Features

1 ch. video networking server for LAN/WAN/Internet
ONVIF conformance
Triple codec: H.264 / MPEG-4 / MJPEG
Resolutions: 4CIF, VGA, QVGA, 2CIF, CIF, SIF, QCIF
Image frame rate: Up to 25 Fps. (at 4CIF)
Two-way audio streaming

RS-485 telemetry control interface
Alarm in / outputs and motion detection
Integrated Web server: 10Base-T/100Base-TX
Pre and post event recording (in client PC)
16 ch. video client software
Power Supply: 12VDC/24VAC, PoE Support

Specifications

Series	eneo NL
System	PAL/NTSC (Auto detection)
Compression standard	H.264, MJPEG, MPEG-4
Ethernet interface	10Base-T, 100Base-TX
Network protocols	IPv4/v6, SMTP, DDNS, HTTP, HTTPS, DNS, FTP, DHCP, QoS, UPnP, NTP, RTSP, RTP, TCP, UDP, SNMP, RTCP, ARP
Configuration	via Smart Setup Software
Stream types	Standard, ROI (Region of Interest) max. 3
Resolution	704x576 ~160x120: 4CIF, VGA, 2CIF, CIF, SIF, QCIF, QVGA (PAL)
Resolution max.	720 x 576
Image transm. rate max.	25 B./Sek.
Frame rate	25 Frps. max. at 704x576 Px. (H.264, MJPEG, MPEG-4, PAL), adjustable
Bandwidth	Adjustable

NLS-1401

(Continuation Spezifications)

Video inputs (amount)	1
Video inputs	1.0Vp-p (C)VBS, (50fps.); NTSC 60fps., 75ohms, BNC, loop-through
Audio support	yes
Audio standards	G.726 ADPCM 40kbps ~16kbps
Audio In-/Output	1/1 Two-way audio streaming
Motion detector	9 zones, ON/OFF switchable
Alarm inputs	yes, 1x TTL
Alarm output	1x Relais NO/NC contact
PTZ Support	yes
Activity detection	yes
Internal storage	no
Pre-alarm recording	up to 5sec.
Post-alarm recording	up to 180sec.
Access	10 Users simultaneous support
Interface	USB 2.0
Serial interfaces	RS-485, Protocols: eneo Fastrax IIE and Pelco D&P
Software update	via Remote Software
Menu languages	English, German, French, Spanish, Italian, Russian
Password protection	yes
External connections	Video (BNC), Audio (Phone jack), USB2.0, Network (RJ-45), Alarm In-put/Output, Factory reset (button), Power Input, RS-485
Power over Ethernet	yes
Supply voltage	12VDC, 24VAC, PoE
Power consumption	5watts
Housing	Aluminium
Colour	Dark grey
Management Software Support	NT-Manager, Nimra, Numina
ONVIF	version 1.01
Certificates	CE
Parts supplied	eVideoClient 16: Viewer and installation software, Wall mount bracket, Manual
Weight	460g
19" Rack mountable	no
Dimensions (HxWxD)	see drawing
Temperature range (Operation)	0°C ~+50°C

Optional accessories

70527	NE-132/AC24V	Power Supply Unit 230VAC/24VAC (1.0A)
70536	VT-PS12DC-9	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, w. open Ends

NLS-1401

93156	NT-MANAGER	Remote Administration Interface Software for eneo NW Series NT, NX, NL
70495	VT-PS12DC-7	Plugable PSU w. Cont. & UK Mains plug-in 100-240VAC/12VDC-1.25A, Regulated
93159	NT-SMARTMANAGER	Utility S/W Tool for eneo Network Series NT, NX, NL

