

Video Security

Cameras | Board Cameras

VK-133/PH

1/3" B/W Board Camera with 3.7mm
Pinhole Lens, 12VDC, 380TVL

Art-No. 91773



Features

CCD B&W Board Camera

1/3" CCD Sensor

Resolution of 420 Horizontal Lines

Electronic Shutter Control (ESC)

Internal Synchronization

High Sensitivity

F3.5/3.7mm Pinhole Lens Element

Supply Voltage: 12VDC

Compact Version

Specifications

System	CCIR, black/white
Imager	CCD, Sony Super HAD Interline Transfer CCD
Sensor size	1/3"
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Synchronization	Internal
Gamma correction	0.45
Sensitivity (at 50% video signal)	0,5Lux, at F1.2 (VT measurement result), 5.6Lux at F4.0
Integration rate	no
Backlight compensation	no
Aperture Correction (APC)	Yes
IR cut filter	no
Mount	n/a
Lens	F4.0/3.7mm (pinhole type)
Application range	security
Nominal format size	1/3"
Aspherical technology	no
Focal length	3,7mm
Horizontal angle of view	65°
Iris control	no

VK-133/PH

(Specifications continued)

Lens mount	integrated lens
Video outputs (type)	VBS
Video outputs	1Vp-p, VBS, 750hm
Serial interfaces	no
Supply voltage	12VDC
Power consumption	1.2watts
Temperature range (Operation)	-10° ~ +50°C
Dimensions (HxWxD)	32x32x14mm
Weight	30 g

Accessories

70448 / VT-PS12DC-6	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, w. open Ends
----------------------------	--

VIDEOR TECHNICAL E. Hartig GmbH
Carl-Zeiss-Straße 8 · 63322 Rödermark · Germany
Telefon +49 (0) 60 74/8 88-0 · Telefax +49 (0) 60 74/8 88-100
info@videortechnical.com · www.videortechnical.com

