

Video Security

Dome Cameras | eneo Vandalism-Proof Fix Domes

VKCD-1311FM/VF

1/3" Colour Dome Camera, In-ceiling Mount
with F1.5/4-9mm Lens, 12VDC, 550TVL

Art-No. 92048



Features

For Wall and In-ceiling Mount
Vandal and Tamper-Resistant
Tinted Lexan Bubble, 100mm
1/3" Colour Board Camera with Super HAD CCD
Integrated F1.5/4-9mm Varifocal Lens w. DC Iris
Resolution of 550 Horizontal Lines

Digital Signal Processing (DSP)
Back Light Compensation (BLC)
Automatic White Balance (ATW)
Manual 3-axis Camera Adjustment
For Easy Indoor and Outdoor Installation (IP65)
Certified according to BGV Kassen

Specifications

Video standard	PAL
System	Colour
Sensor size	1/3"
Imager	CCD, Sony Super HAD Interline Transfer CCD
Active picture elements	approx. 440,000, 752(H) x 582(V)
Synchronization	Internal
Signal-to-noise ratio	48dB
Sensitivity (at 50% video signal)	0,3Lux, at F1.2 (VT measurement result including bubble)
Horizontal resolution	550TVL
Rotation range	manual: 360°
Automatic gain control (AGC)	On/Off switchable
Gamma correction	approx. 0.45
Automatic shutter (AES)	1/50 ~ 1/100.000sec. (not available during Auto Iris ON)
Integration rate	no
Flickerless function	On/Off switchable
White balance (AWB)	Automatic control
Backlight compensation	BLC, On/Off switchable
Aperture Correction (APC)	Horizontal and vertical



VKCD-1311FM/VF

(Specifications continued)

IR cut filter	no
Video outputs (type)	CVBS
Video outputs	1Vp-p, CVBS, 75ohms
Lens mount	integrated lens
Lens type	varifocal
Lens	F1,5 ~ 340/4 ~ 9mm with galvanometer driven iris
Application range	security
Nominal format size	1/3"
Aspherical technology	yes
Focal length	4-9mm
Horizontal angle of view	71-31,6°
Focus range	0.5m ~ ?
Iris control	DC
Mount	n/a
Cable connection	Video (BNC), 12VDC (DC jack)
Serial interfaces	no
Temperature range (Operation)	-10° ~ +50°C
Heater	no
Protection rating	IP65, at installation according to the manual
Supply voltage	12VDC, (9 ~ 15VDC), 12VDC ±0,5V recommended
Power consumption	3.0watts max.
Vandalism resistant	yes
Bubble	100mm diameter, Vandal resistant 3mm -tinted-polycarbonate with high resistance
Colour (bubble)	tinted
Camera adjustment	3-axis camera adjustment: 360° horizontal rotation / +45° tilt rotation, 360° pan rotation
Camera fixing	no
Mounting	in-ceiling mount, wall mount
Housing	indoor housing, Die-cast aluminium with tinted polycarbonate bubble
Housing material	aluminium
Colour (housing)	n/a
Dimensions (HxWxD)	See drawing
Weight	630g
Parts supplied	Mounting screw kit, Torx wrench key, Service monitor cable (Cinch plug), Guide pattern, Manual

Accessories

70447 / VT-PS12DC-5	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug
77773 / VT-PS12DCDT1	PSU 12VDC/1.0A, Regulated, Desktop Version, 1.8m Cables each w. open ends



Maße/Dimensions: mm

VIDEOR TECHNICAL E. Hartig GmbH
 Carl-Zeiss-Straße 8 · 63322 Rödermark · Germany
 Telefon +49 (0) 60 74/8 88-0 · Telefax +49 (0) 60 74/8 88-100
 info@videortechnical.com · www.videortechnical.com