



VM-UHD55M

Article number: 217921

55" (140cm) LCD Monitor, 4K UHD, 3840x2160, LED, USB, DisplayPort, HDMI, DVI, VGA

Professional 55"(140cm) LCD monitor

Maximum resolution 4K UHD 3840x2160 pixels

Media player integrated (USB)

LED Back Light

Perfect presentation through digital 3D filtering and noise reduction

Built to run 24x7x365 continuously

Different video inputs DisplayPort, HDMI, DVI, VGA

Built-in speakers

Including stand

Metal housing (suitable for industrial use)

Specifications

Display:	
Resolution	3840x2160 (16:9)
Synchronization	internal
Aspect ratio	16:9
Resolution pixels	3840x2160
Contrast ratio typical	1100:1
Response time typical	5 ms
Brightness typical	350 cd/m²
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	55"
Screen Size (cm)	140 cm
Pixel format	0,315mm x 0,315mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, DVI, DisplayPort, composite (CVBS), USB2.0
Audio inputs	RCA jack, 2
Serial interfaces	no
General:	
Dimensions (HxWxD)	749,8x1274,8x101mm
Mount	VESA standard 400x200mm
Housing material	metal
Housing color	black
Weight	29kg
Loudspeaker	2
Power consumption	120W
Supply voltage	100 ~ 240VAC, 50/60Hz
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Scope of delivery:	
Parts supplied	manual, IR remote controller, power cord, feet set, VGA cable

Related Products



VM-LCDWMB1 | SKU: 224228

More product information

Mediaplayer function, supported standards: RMVB; MPG; AVI; MP4; JPG; JPEG; PNG at maximum resolution of 1920x1080 pixels.



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

