



# **VMC-19LEDM**

Article number: 208366

19" (48cm) LCD, 1280x1024, Professional Monitor, 12V, Protection Glass, HDMI, LED

Professional PAL/NTSC LCD monitor	Quick signal switching, fast response time
Multi language on-screen menu driven setup	Artifacts, noise and motion blur reduction
Built to run 24x7x365 continuously	Compact metal cabinet, Protection glass
3D comb filter	Integrated loudspeakers
Resolution of 1280x1024	IR remote control included
CVBS,HDMI,RGB and audio input	Rack mount ready, tilt up to 90°

# **Specifications**

Display:	
Resolution	1280x1024 (5:4)
Synchronization	internal
Aspect ratio	4:3
Resolution pixels	1280x1024
Contrast ratio typical	1000:1
Response time typical	5 ms
Brightness typical	250 cd/m²
Backlighting	LED
Viewing angle vertical	160 °
Viewing angle horizontal	170 °
Screen size	19"
Screen Size (cm)	48,2 cm
Pixel format	0.294mm x 0.294mm
Video standard	PAL/NTSC

Features:	
Comb filter	3D Motion Adaptive De-interlace
Menu languages	German, English, French, Italian, Spanish

Interfaces / Inputs / Outputs:	
Video inputs (type)	HDMI, VGA, 2x composite (CVBS)
Audio inputs	RCA, 2
Serial interfaces	no

General:	
Series	eneo VMC
Dimensions (HxWxD)	353x482x80mm
Mount	VESA standard (4 threads M4, 100x100mm)
Housing material	metal
Housing color	black
Weight	6.5kg
Loudspeaker	2
Power consumption	approx. 17W
Supply voltage	12VDC +/-5% (PSU 100V~240VAC included)
Temperature range (operation)	0°C ~ +50°C

Cope of delivery:	
	manual, IR remote controller, VGA cable, power cord. PSU

### **Related Products**



VMC-LCD/WCMB-1 | SKU: 90394





VMC-LCD/WMB-4|SKU: 90468



VM-LCDWMB2|SKU: 224229

#### www.eneo-security.com

### More product information

Flexible tiltable rackmount capability Anti-Burn-in Technology

