



VMC-8LCD-CP01B

Article number: 203669

8,0" (20.3cm) LCD Monitor, 1024x768, 12VDC, Pedestal, Silvergrey

8" (20.3cm) display screen size	Built-in speaker
PAL/NTSC auto selection	Angled monitor stand included
Multi language on-screen menu control	Supply voltage: 12VDC/24VDC
Resolution of 1024x768 px.	Robust plastic cabinet
2x CVBS, RGB and audio input	Different ranges of application

Specifications

Display:	
Resolution	1024x768 (4:3)
Synchronization	internal
Resolution pixels	1024x768
Contrast ratio typical	500:1
Response time typical	50 ms
Brightness typical	250 cd/m ²
Viewing angle vertical	135 °
Viewing angle horizontal	140 °
Screen size	8"
Screen Size (cm)	20,3 cm
Pixel format	1024(H)x768(V)
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Menu languages	English, German, French, Spanish, Italian, Korean, Japanese
Interfaces / Inputs / Outputs:	
Video inputs	CVBS: 1Vp-p, 75ohms, Cinch Y/C: Y= 0.7Vp-p, C= 0.3Vp-p, 75ohms, 4-pin MiniDIN
Video inputs (type)	composite (CVBS), VGA
Audio inputs	Mono input, 400mVrms, 1
Serial interfaces	no
General:	
Dimensions (HxWxD)	see drawing
Mount	Angled stand and 4x threads M3 50x55mm, for wall mounting (see drawing)
Housing material	plastic
Housing color	silver grey
Weight	0.65kg
Loudspeaker	0.5watts
Power consumption	10W
Supply voltage	12VDC +/-5% (Power supply unit included)
Temperature range (operation)	-10°C ~ +60°C
Scope of delivery:	
Parts supplied	Monitor stand, PSU 100~240V/12VDC with power cord, Multiple connection cable (Power IN, CVBS IN, Audio IN), VGA cable, Cigarette lighter adapter cable, AV adapter cable, Cinch/BNC adapter, IR remote control unit, Multiple language manual

Related Products



VMC-LCD/WCMB-1 | SKU: 90394



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

