



## Monochrome Monitors

FDP-No.: 90356

### VMM-20

- 20" High Resolution Picture Tube
- Resolution of 900 Horizontal Lines
- Video / Audio Loop-through Inputs
- Built-in Loudspeaker
- Over /Underscan Function
- Universal Voltage Input
- Rugged Metal Housing
- Detachable Power Cord



### Specifications:

|                              |   |
|------------------------------|---|
| Screen size                  | 20" (51 cm)   |
| Screen size (visible)        | 18.5" (47 cm)   |
| System                       | CCIR/EIA  |
| Scanning frequency range H/V | 15625 / 50 Hz<br>15750 / 60 Hz  |
| Horizontal resolution        | 900 TV lines  |
| Video inputs                 | 2x 0.5-2.0 Vp-p, CVS, automatic 75 Ohm termination (loop-through)   |
| Audio input                  | 1x 300 mVrms (loop-through)   |
| Over-/ under scan function   | 10% / 6%  |
| Synchronization              | Internal  |
| Loudspeaker consumption      | 2 W   |
| Connectors                   | Video loop-through inputs (BNC), Audio loop-through input (Cinch), Voltage input                                      |
| Operations (Front part)      | V-/H-Size, V-/H-Hold, Brightness, Contrast, Sharpness, Volume, Over-/Underscan selector, Input selector, Power ON/OFF |
| LED indication               | Channel A/B, Power-ON   |
| Operations (back part)       | V-Linearity, DC-Restoration switch  |

## VMM-20

---

|                    |  |
|--------------------|--|
| Supply voltage     | 230 VAC/50 Hz, 120 VAC/60 Hz (90 to 254 VAC, 50/60 Hz) |
| Power consumption  | 45 W   |
| Temperature range  | 0° to +40°C  |
| Housing            | Steel (with plastic front)                             |
| Colour             | Light grey   |
| Dimensions (HxWxD) | 442x445x380 mm   |
| Weight             | 17.7 kg  |
| Special features   | Detachable power cord                                  |

e-mail: [info@eneo-security.com](mailto:info@eneo-security.com) • [www.eneo-security.com](http://www.eneo-security.com)