



Quad Units EDP-No.: 72361

## VT-6041/427C

- · Display of 4 B&W Pictures on one Screen
- Real Time Refresh Rate
- Resolution: 1024x512 Pixels
- Video Loss Detection, "Freeze" of the last Picture
- Programming via On-screen Menu
- Remote Control via PC or Wired Remote Control Unit
- Option: 19" Rack Mount Kit



## Specifications:

Video inputs 4x 1 Vp-p, 75 ohms, loop-through

VCR input 1 Vp-p, 75 ohms

Video outputs 1x 1 Vp-p, 75 ohms (full screen and Quad display)

1x VCR 1 Vp-p 75 ohms (Quad display only)

Digital zoom on VCR playback Y

Time/date display Built-in clock with back-up battery, Format: YY-MM-DD /

HH:MM:SS

Camera title display 6 characters

Set-up via on-screen menu Yes

Resolution 1024x512 Pixels

Grey scales 256

Refresh rate 25 fields per sec.

Freeze of single Quad pictures Yes

Adjustable dwell time Yes (1-99 sec.)

Alarm inputs

Alarm output 1x NO/NC contact (1 A/24 VDC rated)

Hold time 1 sec. to non-stop (adjustable)

Alarm reset Automatic reset after the pre-selected alarm hold time,

or via the alarm reset input, or by pressing a button



## VT-6041/427C

Alarm buzzer Yes (switchable)

Alarm called full screen Yes

Video gain adjustment +/-2db for each channel

Keyboard locking Yes (Lock button)
Supply voltage 24 VAC 50/60Hz\*

Power consumption 10 W
Serial interface RS-232

Temperature range 0°C to +50°C

Housing Steel with plastic front

Colour Pantone 427C

Dimensions (HxWxD) 44.4x430x200 mm

Weight 2.5 kg

## Additional descriptions

\*) Plug-in transformer 230 V/24 VAC included

Accessories	
EDP No. / Type	Description
72284 VT-6041FB	Remote control unit for VT-6041 quad splitters
72286 VT-6000/7000RMK	19" Rack mount kit for quad splitter series VT-6041 to VT-6054 and
	multiplexer series VBM/VCM-700x

e-mail: info@eneo-security.com • www.eneo-security.com