

Product information

Focusing on
tomorrow, caring
for today

EQ 250 HQ

1/3" colour digital camera,
standard resolution



Specifications

Sensor: 1/3" SONY CCD
Picture element: 500 (H) x 582 (V)
Horizontal resolution: 380 TV lines
Sensitivity: 0,3 lux / F = 1.2
Video output: 1 Vp-p composite PAL, BNC
Audio: microphone output 500 mV / 47 kOhm, Cinch
S/N ratio: over 48 dB
Gamma correction: > 0,45
White balance: digital auto tracing
Back light compensation: on / off
AGC: on / off
Synchronisation: internal or line-lock with V-setup
Electronic shutter: on / off, 1:50 ~ 1:100.000
Flickerless function: on / off
Lens control: VD / DD switchable
Lens mount: C/CS mount, full range backfocus mechanism

Power source:

EQ 250 HQ A / P: 12 V DC / 24 V AC
EQ 250 HQ / P: 90 ~ 260 V AC

Power consumption:

EQ 250 HQ A / P: 5 W max.
EQ 250 HQ / P: 9 W max.

Ambient temperature: 0°C ~ +50°C

Dimensions: 57 (W) x 51 (H) x 140 (D) mm

Weight: 600 g (EQ 250 HQ), 500 g (EQ 250 HQ A)

