



SPECIFICATIONS

Pickup Device	: 1/3", Super HAD CCD
Picture element	: 752(H) x 582(V)
Scanning	: 2:1 interlaced
Video Output	: 1Vpp composite PAL, BNC
Audio	: microphone output 500mV / 47KOhm, 40Hz-12KHz (-3dB), Cinch
S/N Ratio	: > 48 dB
Horizontal resolution	: 480 TV lines
Sensitivity	: 1 Lux / F1,2
White balance	: automatic
BLC	: ON / OFF
AGC	: ON / OFF
Synchronisation	: internal or line-lock with V-adjustment
Electronic shutter	: ON / OFF, up to 1:100.000
Flickerless function	: ON / OFF
Gamma correction	: > 0,45
Lens drive	: Direct Drive / Video Iris
Lens mount	: C / CS
Power source	: EQ350 P/A: 24 VAC / 12 VDC EQ350 P : 90 ~ 260VAC
Power consumption	: EQ350 P/A: 5 W max. EQ350 P : 9 W max.
Operating Temperature	: 0°C ~ 50°C
Dimensions	: 57 (W) x 51 (H) x 140,2 (D) mm

Due to continued improvement, specifications are subject to change without prior notice.

EverFocus® Electronics (Europe) GmbH

Albert-Einstein-Str. 1, 46446 Emmerich

Phone: +49 (0) 28 22 9394 0, Fax: +49 (0) 28 22 93 94 95

Internet: www.everfocus.de, email: info@everfocus.de