

**EverFocus®****EZ180****Product Information**

1/3" high resolution weatherproof b/w camera

AC/DC  
24 V / 12 Vb/w  
CCIRL.L.  
ON/OFFAGC  
ON/OFFBLC  
ON/OFFES  
1/100.000A.I.  
DD**SPECIFICATIONS**

Pickup Device	: 1/3 " CCD
Picture element	: 752(H) x 582(V)
Scanning	: 2:1 interlaced
Video Output	: 1Vpp composite CCIR, BNC
S/N Ratio	: > 48 dB
Horizontal resolution	: 560 TV lines
Sensitivity	: 0,1 Lux / F1,2
BLC	: ON / OFF
AGC	: ON / OFF
Synchronisation	: internal or Line-Lock with V-adjustment (with 24 VAC only)
Electronic shutter	: ON / OFF, up to 1:100.000
Flickerless function	: ON / OFF
Gamma correction	: > 0,45
Lens	: EZ 180 V1: varifocal 3,5-8mm : EZ 180 V2: varifocal 9-22mm
Lens F-stop range	: 1,6 ~ 360
Lens drive	: Direct Drive
Heater	: 12 W thermostat controlled, activated < 10°C
IP Safety Class	: IP-66
Power supply	: 24 VAC / 12 VDC
Power	: 3 W max., 15 W with activated heater
Operating Temperature	: -46°C ~ 50°C
Dimensions (BxHxT)	: 83 x 70 x 172 mm (with sunshield) : 57 x 57 x 132 mm (without sunshield)

Due to continued improvement, specifications are subject to change without prior notice.

**EverFocus®** Electronics (Europe) GmbH

Albert-Einstein-Str. 1, 46446 Emmerich

Phone: +49 (0) 2822 9394 0, Fax: +49 (0) 2822 9394 95

Internet: [www.everfocus.de](http://www.everfocus.de), email: [info@everfocus.de](mailto:info@everfocus.de)