

**EverFocus®****Product Information****EZ300**

1/3" high resolution weatherproof colour camera

AC/DC
24 V / 12 VColour
PALL.L.
ON/OFFAGC
ON/OFFBLC
ON/OFFES
1/100.000A.I.
DO**SPECIFICATIONS**

Pickup Device	: 1/4 ", CCD
Picture element	: 752(H) x 582(V)
Scanning	: 2:1 interlaced
Video Output	: 1Vpp composite PAL, BNC
S/N Ratio	: > 48 dB
Horizontal resolution	: 480 TV lines
Sensitivity	: 1 Lux / F1,2
White balance	: automatic
BLC	: ON / OFF
AGC	: ON / OFF
Synchronisation	: internal or Line-Lock with V-adjustment (with 24 VAC only)
Electronic shutter	: ON / OFF, up to 1:100.000
Flickerless function	: ON / OFF
Gamma correction	: > 0,45
Lens	: EZ 300 V1: varifocal 3,5-8mm EZ 300 V2: varifocal 9-22mm
Lens F-stop range	: 1,6 ~ 360
Lens drive	: Direct Drive
Heater	: 12 W thermostat controlled, activated < 10°C
IP Safety Class	: IP-66
Power supply	: 24 VAC / 12 VDC
Power	: 5 W max., 15 W with activated heater
Operating Temperature	: -46°C ~ 50°C
Dimensions (BxHxT)	: 83 x 70 x 172 mm (with sunshield) 57 x 57 x 132 mm (without sunshield)

Due to continued improvement, specifications are subject to change without prior notice.

EverFocus® Electronics (Europe) GmbH

Albert-Einstein-Str. 1, 46446 Emmerich

Phone: +49 (0) 2822 9394-0, Fax: +49 (0) 2822 9394-95

Internet: www.everfocus.de, email: info@everfocus.de