

# CCTV Monitors

## Colour CCTV monitors

FH 7415 HR



FH 7419 HR



FH 7421 A-T



Item code	FH 7415 HR	FH 7419 HR	FH 7421 A-T
Description:	15" colour monitor, high resolution	19" colour monitor, high resolution	21" colour monitor
Video format:	PAL / NTSC		
Picture tube:	15", 0,27mm stripe pitch	19", 0,27mm stripe pitch	21", 0,7mm stripe pitch
Horizontal resolution:	> 800 lines	> 800 lines	> 500 lines
Input connector:	2 x composite BNC, 1 x S-video	2 x composite BNC, 1 x S-video	2 x composite BNC, 1 x S-video
Input signal:	1 Vp-p	1 Vp-p	1 Vp-p
Input impedance:	75 Ohm	75 Ohm	75 Ohm
Audio (input / output):	yes (3/3)	yes (3/3)	yes (3/3)
Dimensions:	368 (W) x 361 (H) x 376 (D) mm	448 (W) x 434 (H) x 448 (D) mm	492 (W) x 474 (H) x 482 (D) mm
Weight:	15,0 kg	25,0 kg	27,0 kg
Power source:	100 ~ 240 V AC, 50 / 60 Hz	100 ~ 240 V AC, 50 / 60 Hz	100 ~ 240 V AC, 50 / 60 Hz
Power consumption:	95 W max.	95 W max.	80 W max.
Operating temperature:	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C

## b/w CCTV monitors

FH 7312



FH 7315



FH 7320



Item code	FH 7312	FH 7315	FH 7320
Description:	12" b/w monitor	15" b/w monitor	20" b/w monitor
Video format:	CCIR / EIA		
Picture tube:	12"	15"	20"
Horizontal resolution:	> 800 lines	> 1000 lines	> 1000 lines
Input connector:	1 x CCIR BNC	1 x CCIR BNC	1 x CCIR BNC
Input signal:	1 Vp-p	1 Vp-p	1 Vp-p
Input impedance:	75 Ohm	75 Ohm	75 Ohm
Audio:	no	no	no
Dimensions:	304 (W) x 320 (H) x 310 (D) mm	350 (W) x 353 (H) x 360 (D) mm	472 (W) x 450 (H) x 360 (D) mm
Weight:	8,0 kg	12,0 kg	20,0 kg
Power source:	100 ~ 240 V AC, 50 / 60 Hz	100 ~ 240 V AC, 50 / 60 Hz	100 ~ 240 V AC, 50 / 60 Hz
Power consumption:	30 W max.	35 W max.	36 W max.
Operating temperature:	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C