

FH 7519 T

19" TFT monitor



Specifications

LCD Display: 19" active matrix TFT LCD panel

Viewable size: 376,32 (H) x 301,056 (V) mm / 5:4

Contrast ratio: 500:1 (typ.)

Brightness: 250 cd / m² (typ.)

Response time (tr/ta): 15/10 ms (typ.)

Display colour: 16,7 million

Pixel pitch: 0,294 (H) x 0,294 (V) mm

Max. resolution: 500 TV lines / 1280 x 1024

Horizontal frequency: 30 K ~ 80 KHz

Vertical frequency: 56 Hz ~ 75 Hz

Viewing angle H/V: 170° / 170°

Display mode: Video, S-Video, VGA/SVGA/XGA/SXGA, YCbCr

Signal connector: Video 1,0 Vp-p, 75 Ohm / BNC in/out,

audio in/out, 15-pin Mini D-Sub, YCbCr in

Audio speaker: 1 W (max.)

OSD menu: VGA: Brightness, contrast, H-Pos., V-Pos., clock, phase, colour temp., user colour R/G/B, OSD H-Pos. / V-Pos., volume, PiP, language, recall

Video: colour, tint (NTSC only), brightness, contrast, sharpness, H-Pos., volume, language, colour temp., scan, PiP, recall

Power input: DC input: 12V / 4,16 A

Operating condition: Temp. 0°C ~ +40°C, humidity 10-85%

Storage condition: Temp. -20°C ~ +60°C, humidity 10-85%

Power consumption: 50W (max.)

Power management: VESA DPMS compatible (75x75mm)

Dimensions: 420,6 (W) x 405,3 (H) x 170 (D) mm

Weight: 6,3 kg

Safety: FCC, CE (EMC/LVD), UL, CUL

Wall mounting accessories: BA DW 151 / 161, BA DW 170 / 171

Further accessories: BA RK 19 – 19" rack mount bracket

