

WIT 7" MONITOR POE BLACK MEET



Reference: 14703

WIT is a capacitive touch screen monitor available in 7" and 10" versions. WIT graphical interface provides an intuitive user experience since it is design focused on a residential intercom use.

F...

DESCRIPTION

WIT is a capacitive touch screen monitor available in 7" and 10" versions. WIT graphical interface provides an intuitive user experience since it is design focused on a residential intercom use.

FEATURES

- Capacitive Touch Screen (7" / 10")
- Hands Free Audio Communication
- High definition colour TFT
- Different ringtones depending on call source
- 3 Different colour options (white, black, gold)
- Remote firmware upgrade
- Android based
- Available in 8 languages (English, Spanish, German, Polish, Russian, Hebrew, Turkish, Chinese)
- Door bell connection with IP camera visualization
- IP CCTV visualization (up to 8)
- Aux IP CCTV camera visualization and aux relay operation during call (up to 4)
- Relay activation (up to 8 using relay module)
- Home Automation Ready through Apps (in 7" and 10")
- Automatic and Manual Picture Capture
- Integrated 7 zones alarm + tamper

FUNCTIONS

1. CONCIERGE

Users can call the desired concierge by selecting it on the list shown in the user interface. If the concierge has a camera attached a video communication will be stablished, otherwise only audio.

2. PANEL AND CCTV CAMERA AUTO ON

Users can open the panel's video channel of their respective block for surveillance purpose. This can be done by selecting the panel the user wants to supervise or the CCTV camera to visualize. Once the panel communication is established, the user can take pictures, talk and open the door if wanted.

3. AUX CAMERA AND AUX DOOR LOCK RELEASE DURING CONVERSATION

When a call is received from the panel, it is possible to display different aux cameras (up to 4) to get a different angle of view or to follow the visitor. At the same time different aux relays (up to 4) can be activated to open additional gates or barriers.

4. VIDEO DOOR BELL



It is possible to connect a pushbutton to the monitor so it will trigger the doorbell sound on the monitor. The door bell call can automatically display the video coming from an IP CCTV camera, increasing the security.

5. HOME TO HOME CALL

The monitor allows the users to call different apartments within the same community.

6. CALL LOG

Users can have a clear view of their call history in the CALL LOG interface and are able to browse through the pictures taken for each call.

7. PHOTO CAPTURE

When receiving a call, it is possible to capture automatically a photo. It is possible to take additional photos if desired.

8. MESSAGES

Users can receive text messages from their property management so they can easily know if there is a package, a maintenance schedule or an import event on their community (software management required). Maximum 64 messages.

9. LIFT CONTROL

Tenants can enable the lift to their visitors to access their floor at the same time the panel door lock is opened from the monitor. Tenants can call the lift before leaving their apartment, so the lift car is ready on the floor.

10. ALARMS

The monitor provides 7 alarm zones management, managed under 3 simple modes:

HOME: Lowest Security level. SLEEP: Medium Security level. OUT: Highest Security level.

11. SOS

User generates an SOS alarm by touching this icon several seconds, sending a message to the concierge and management software.

12. DO NOT DISTURB

It is possible to set the monitor to DO NOT DISTURB mode, so the calls will not produce any sound during a defined period of time. Do not disturb led will light up if this function is active.

REFERENCES

WIT 7" 14701 WIT 7" MONITOR POE WHITE 14703 WIT 7" MONITOR POE BLACK 14704 WIT 7" MONITOR POE GOLD 9541 WIT / MIO CONNECTOR

WIT 10" 14811 WIT 10" HOME AUT. MONITOR POE WHITE 14813 WIT 10" HOME AUT. MONITOR POE BLACK 14814 WIT 10" HOME AUT. MONITOR POE GOLD 1489 WIT 10" WALL FLUSH BOX

TECHNICAL SPECIFICATIONS



System: CPU: Quad-core FLASH: 4GB SDRAM: 512 MB

Screen: 7 and 10 inch format Capacitive touch screen Format: 16:9 Resolution: 1024x600 Brightness: 7" 200cd/m2; 10" 220cd/m2 Contrast: 7" 400/1; 10" 450/1 View Angle: 7" 160° Horizontal, 130° vertical; 10" 120° Horizontal, 110° Vertical

Audio/Video Features:
G.711 audio codec
H.264 video codec
RTSP compatible for CCTV IP cameras
Audio level adjustable on conversation and mute
Hands-free operation
Private communication
Selectable call melodies based on call origin

Power Consumption: On standby: 200 mA (7") / 210 mA (10") Conversation: 500 mA (7") / 600 mA (10")

Working voltage: PoE 12 Vdc

Connectivity: 1 x Ethernet RJ-45 (WIT 7") 2 x Ethernet RJ-45 (WIT 10") for building and apartment network isolation. Doorbell input (1 alarm zone input) Panic button input (1 alarm zone input) Built in web server for configuration and remote management

Working Environment: Temperature: -10 oC .. +55 oC Humidity: 20 – 85% (Non-condensing) IP: 30

Weight: 0,8685 kg

Size of product when packed: 6,8x31x21,5 cm

EAN 13: 8,4243E+12