

C-Allview Camera

C-Allview Camera





The performance features at a glance

- Day/night camera
- High-speed pan-and-tilt system
- 18x zoom and 36x zoom
- Vandalism-proof
- Protection class IP67
- Built-in wiper unit




Simply everything in view

The new C-Allview camera misses virtually nothing, whether by day or at night. Fitted with a high-speed pan-and tilt head, it pans through more than 180° per second in constant rotation, can be titled up to 290° and reacts in a flash in any position. The day/night camera contains a zoom lens with a focal length of 4.1 mm – 73.8 mm. Thanks to this 18x zoom option, essential impressions can be captured in excellent image quality. Additionally it is available as 36x zoom version with lens of 3.4 - 122.4 mm focal length.

Order data

| 0.40.000 | | |
|----------------------------------|---|--|
| Order number | Product description | |
| C-ADN3X18YPT-W C-ADN3X18YPT-B | PTZ speed day/night camera in outdoor housing (IP67), 18x optical zoom, 4.1 – 73,8 mm, 1/4" CCD (ExView), 480 lines, colour 0.7 lux, b/w 0.01 lux (F 1.4), vandalism proof, incl. wiper unit, bracket and external power supply unit (230 VAC/24 VAC) in weatherproof housing, matt white or black | |
| C-ADN3X36YPT-W C-ADN3X36YPT-B | PTZ speed day/night camera in outdoor housing (IP67), 36x optical zoom, 3.4 – 122,4mm, 1/4" CCD (ExView), 530 lines, colour 1.0 lux, b/w 0.015 lux (F 1.4), vandalism proof, incl. wiper unit, bracket and external power supply unit (230 VAC/24 VAC) in weatherproof housing, matt white or black | |
| C-AWN | Screen washer nozzle with supply line and mounting assembly | |
| C-AWA5L | Screen washer pump and 5-litre water tank, 24 VAC | |
| C-AWA25L | Screen washer pump and 25-litre water tank, 24 VAC | |
| C-AS | Sunshield, for suspended installation, with mounting accessories on request | |
| C-PM-W/C-PM-B | Swan-neck bracket for mounting on pole, matt white or black | |
| C-WM-W/C-WM-B | Wall mounting bracket for suspended installation, matt white or black | |
| C-PPM-W/C-PPM-B | Ceiling mount for pendant mounting, white or black | |
| C-10m | Multi core replacement cable with plug connection, 10 m | |
| C-EXTPSU24VAC | Replacement power supply unit in the weatherproof housing, 230 VAC/24 VAC, IP67 | |
| РТВ | Wall bracket 45.8 cm, for vertical installation, RAL9002 | |
| C-KBD2 | Control unit (3-axis) for control ZC-PT and C-Allview series, control by DVR touch panel display | |
| | | |







Steadfast even in a tough environment

Made from sturdy, powder-coated aluminium, the housing of the C-Allview is vandalism-proof and, as a result, can be deployed at many locations. It was specially designed for monitoring dangerous and endangered locations, for example prisons or motorways. It is also particularly resistant against scratches or oxidation, and even against targeted attacks.

Provided with the protection class IP67, even extreme weather conditions do not hinder the installation of the camera outdoors. This is possible thanks to convenient mounting either as a ceiling or wall installation.



Always remaining clean ...

is not a problem for the C-Allview. In contrast to conventional dome cameras, it is possible to keep the lens surface clean using a wiper unit included in the scope of delivery. Dirt or water is therefore removed quickly and simply from the additionally reinforced face-plate; a washer unit is available as an option. So nothing stands in the way any more of a completely clear view and the wiper unit can be removed at any time.

Another major advantage is gained from the lack of a lower dome and so there is absolutely no aberration in the image. That means a constantly sharp image of the object being viewed.

CBC (Deutschland) GmbH CBC (Poland) Sp.z.o.o D-40549 Düsseldorf T: +49-(0)211 53 06 70 F: +49-(0)211 53 06 71 80 info@cbc-de.com

www.cbc-de.com

CBC Russia Moscow Rep. office Ul. G. Morcinka 5. Paw 6 RU-115054 Moscow PL-01496 Warszawa T: +48-(0)22 6 38 44 40 T: +7-495 7 10 88 83 F: +48-(0)22 6 38 45 41 F: +7-495 7 10 88 84

info@cbc.ru

CBC (Europe) Ltd. 7/8 Garrick Industrial Centre, Irving Way UK-NW9 6AO London T: +44-(0)20 87 32 33 10 F: +44-(0)20 82 02 33 87 info@cbcuk.com

www.cbceurope.com

CBC (Europe) Ltd. Ufficio di Milano Via E. Majorana, 2 I-20054 Nova Milanese T: +39-0362 36 50 79 F: +39-0362 4 00 12 info@cbceurope.it www.cbceurope.it

ect to technical changes and errors 112008

C-Allview Camera



| Technical specifications | C-AllView |
|---------------------------------|---------------------------------------|
| Video system | PAL/NTSC |
| Video output | 1.0 Vp-p; 75 Ohm |
| Image sensor | 1/4" IT-CCD (Exview) |
| Effective elements (H x V) | 752 x 582 |
| Horizontal resolution TVL | 480 lines |
| Min. illumination (colour) | 0.7 lux |
| Min. illumination (mono) | 0.01 lux |
| Max. aperature ratio | 1:1.4 – 1:3.0 |
| Focal length | 4.1 mm – 73.8 mm or 3.4 mm – 122.4 mm |
| Horizontal angle of view | 48° – 2.7° |
| Zoom | 18 x or 36 x optical, 12 x digital |
| Focus | auto/manual |
| S/N ratio | >50 dB |
| Electronic shutter | 1/1 to 1/10,000 s |
| Synchronisation | internal, line-lock |
| Gamma characteristics | 0.45 |
| White balance | ATW, AWB |
| Backlight compensation | auto/manual -3 ~ 28 dB, in 2 dB steps |
| Video gain and lift | auto/manual -3 ~ 28 dB, 16 steps |
| Pan range | continuous 360° |
| Tilt range | 290° |
| Pan/tilt speed | >180°/s |
| Preset accuracy | (0.1°) 14 bit resolution encodes |
| Preset positions | 32 |

| Technical specifications | C-AllView |
|---------------------------------|---|
| Preset tours | 16 |
| Cruise | 4 x 1 minute, individual |
| Preset Tilting | 0° or 35° |
| Day/night toggling | Yes |
| Electronical flip | Yes |
| Privacy zones | 24, with seperate algorithms to account for offset tilt of head unit or inverted operation (max. 8 on the screen simultanous, image reversal off) |
| Protocols | Pelco P, Pelco D, BBV coaxial, VTC, Sensormatic (RS-422), Samsung SCC300, Kalatel, C-Dome |
| Controller interface | RS-485 half duplex data communication |
| Coaxial telemetry | Optional |
| Alarm | support 8 x 8 Alarm inputs on RS-485 bus to PTZ unit (by external alarm card in power supply) |
| Wiper | Yes |
| Vandal resistance | Yes |
| IP rating | IP67 |
| Housing colour | matt black or RAL9002 |
| Mount type | Normal or inverted |
| Mounting options | standard mount, 4" (101.6 mm) PCD |
| IR mode | via external input |
| Operating voltage | 20 - 36 VDC/14 - 26 VAC |
| Power consumption | max. 15 W |
| Operation temperature | -20°C ~ +50°C |
| Weight | 7 kg |
| Dimensions (Ø x H) | max. 220 mm x 268 mm |

