

C-ALLVIEW

High Speed Rugged Pan / Tilt Cameras

C-ALLVIEW



GANZ

GANZ IS PART OF THE CBC FAMILY

C-ALLVIEW

High Speed Rugged Pan / Tilt Cameras



Perfect Partners



Keyboard-C-KBD2



IR lamps

KEY FEATURES:

- Vandal resistant
- Flexible mounting options
- Flat toughened glass window
- Day/Night camera
- High-speed, pan-and-tilt system
- 530TVL 18x & 36x optical zoom camera options
- Protection class IP67
- Built-in wiper unit
- Presets and tours
- 18 Protocols
- Camera, bracket, PSU and 10 meter cable supplied
- Nudge correction
- Quick Tilt
- WDR
- Mosaic privacy zones

The C-AllView day/night high speed PTZ Camera is a continuous rotation "ruggedised" PTZ camera, sealed to IP67 and designed to be installed in harsh and challenging environments or areas where the camera unit may be liable to experience physical abuse.

The optically flat glass is distortion free giving brighter clearer images at higher zoom ranges and resolutions thus allowing the C-AllView to see further and in more detail than ever before.

The C-AllView PTZ camera has been cast from aluminium, hard anodised and powder coated to protect from scratching, oxidation or attack from solvents, making it vandal resistant and suitable for most applications.

The C-AllView can be mounted inverted, upright or inclined using the Quick Tilt facility, this virtually eliminates any blind spot when mounted in the upright position.

C-AllView makes use of the latest camera module technology and included as standard is a 530TVL high resolution camera with the option to use Wide Dynamic Range (WDR) and mosaic privacy masks.

Ordering Codes:

C-ADN3X18YPT-W	1/4" Day/Night PTZ camera, 18:1, White
C-ADN3X18YPT-B	1/4" Day/Night PTZ camera, 18:1, Black
C-ADN3X36YPT-W	1/4" Day/Night PTZ Camera, 36:1, White
C-ADN3X36YPT-B	1/4" Day/Night PTZ Camera, 36:1, Black

Accessories

C-AWN	60mm PCD Screen washer nozzle, manifold & mounting assembly
C-AWA5L	Washer unit 24Vac 5 litre capacity
C-AWA25L	Washer unit 24Vac 25 litre capacity
PB180	2 x IR Lamp Bracket
PB360	4 x IR Lamp Bracket
C-A20P	20 meter extension cable (pre-plugged)

Mounting brackets

C-WM-B	Wall mount bracket c/w lanyard clip (Black)
C-WM-W	Wall mount bracket c/w lanyard clip (White)
C-PM-B	Pole mount swan neck bracket c/w lanyard clip (Black)
C-PM-W	Pole mount swan neck bracket c/w lanyard clip (White)
C-CMA-B	Corner Adaptor to suit C-WM-B (Black)
C-CMA-W	Corner Adaptor to suit C-WM-W (White)
C-PPM-B	Pendant Pole mount bracket (1 meter) (Black)
C-PPM-W	Pendant Pole mount bracket (1 meter) (White)
UPCA1	Universal pole clamp adaptor

C-ALLVIEW

High Speed Rugged Pan / Tilt Cameras

C-ALLVIEW

The advantages for the installer are obvious: easy to install and simple to set up via a few dip-switches and a comprehensive OSD accessible via any keyboard or matrix on the market today.

Eighteen different protocols (including two up-the-coax) are loaded as standard giving even more flexibility to existing installations without having to order special variants.

The nudge correction feature is there to protect the camera against knock and bumps in incredibly difficult environments. If the camera is forced from its current position or tour it will wait one second then immediately return to the exact position before it was knocked out of alignment without any chance of damage to gears or to the industrial quality stepper motors.

The wiper and optional wash facility on the C-AllView is ideal for all weather conditions. With the remote operation of the wash and optional wipe facility the operator can have clearer images from the comfort of the control room.

The Quick Tilt facility allows the mounting arms to be tilted forward to give a complete 360 degree coverage with minimum blind spots.

Wash/wipe facility enables cleaning of the front glass easily without the need to make a costly maintenance visit ensuring minimum disruption.


Both downward views and upward views are possible making the C-AllView a highly versatile and adaptable solution.

Flat front glass is distortion free enabling crystal clear images even when using 530TVL resolution camera modules and 36x optical zoom ratios.

A PB180 or PB360 bracket can be fitted between the pole or pendant mounting points on the C-Allview to accept the range of CBC vari focal IR illuminators.



Pole or pendant mounting positions are a standard feature of the C-AllView and finish can be in matt black or matt white.



C-ALLVIEW

High Speed Rugged Pan / Tilt Cameras

Model	C-ADN3X18PT	C-ADN3X36YPT
Video System	PAL / NTSC	
Video Output	1.0 V (p-p) / 75	
Image Sensor	1/4" IT CCD	
Horizontal Resolution	530 TVL	530 TVL
Minimum Illumination (50 IRE)	0.7 lux colour, 0.07 lux mono @ F1.4	1.4 lux colour, 0.01 lux mono @ F1.6
Horizontal Viewing Angle	2.8 - 48 degrees	1.7 - 57.8 degrees
Effective Elements	752 (H) x 582 (V)	
Zoom	18 x optical, 12 x digital	36 x optical, 12 x digital
Lens	4.1 - 73.8 mm	3.4 - 122.4 mm
S/N Ratio	>50 dB	
Sync System	INT. /L.L.	
Gamma Characteristic	0.45	
White Balance	ATW, AWB	
Backlight Compensation	Yes	
Pan Rotation	Continuous	
Tilt Rotation	290°	
Pan & Tilt speed	> 180° per second	
Pan Coverage	360 degrees (continuous rotation)	
IP Rating	IP 67	
Mount Type	Upright, Inclined and Inverted	
Preset Accuracy	14 bit resolution encodes (0.1 degrees)	
Preset Positions	32 (256)	
Preset Tours	16	
Mimic Tours	4 x 1 mimic tours	
Video gain and lift	16 steps	
Preset Titling	Yes	
Privacy zones	24 opaque or mosaic, with separate algorithms to account for offset tilt of head unit or inverted operation (12 privacy zones if E-flip is enabled)	
Protocols	CBC, OCP, 360 Vision, DeView, Forward Vision, Ikegami, Kalatel, Pelco D, Pelco P, Philips, Samsung, Sensomatic, Ultrak/Honeywell, VCL, Baxall DC, BBV Coaxial, Pelco Coaxitron, Dennard, BBV 485	
Controller Interface	RS-485 half duplex data communication Coaxial Telemetry Optional	
Alarm	Supports 64 alarms on RS485 bus, external to PTZ unit	
Real Time Clock	Yes	
Mounting Options	4" (101.6mm) PCD, 60mm PCD	
Housing Colour	Matt Black (RAL 9011) or Matt White (RAL 9002)	
Power Supply	20-36 V DC / 14-26 V AC	
Vandal Resistant	Yes	
Operating Temperature	-20°C ~ +50°C, Relative humidity 90%	
Operating Voltage	20-36 VDC / 14-26 VAC	
Power Consumption Max	30W	
Dimensions	220(W) x 368.15(H) mm	
Weight	7 kg	

Features and specifications are subject to change for further improvement without any notice

Note:

Some of the supported devices listed above are not manufactured by CBC (Europe). It is therefore possible that the protocols have been changed from the original manufacturer or are in different configurations from the units previously tested by CBC (Europe).

CBC (Europe) recommends that a compatibility bench test prior to installation of the complete system is carried out to ensure complete functional requirement. CBC (Europe) will not be liable for any installation costs or lost revenues in the event of any compatibility problems where they occur.



CBC (EUROPE) Ltd.

7/8 Garrick Industrial Centre, Irving Way, London NW9 6AQ, England
tel: technical support +44 (0)20 8732 3350 +44 (0)20 8732 3353 www.cbceurope.com