

C-MPH16-II

16 Channel H.264 Network DVR with DVD Writer



The C-MPH-II 16 Channel range of DVRs are based upon years of research and development in the Digital Video recording market. The DVRs not only allow you to Record, View, and Play back your images using the latest H.264 video compression but also allows a user to view live images and playback information on the same display whilst backing up previous events. Recording is uninterrupted during this process and up to 5 others can view the DVR via a network at the same time.

In an era of personal mobile communication made available by the introduction of smart phones. The C-MPH-II range of DVRs also allow to connect to your DVR and view your images via your mobile phone including iPhone[®], Black-Berry[®], Windows Mobile, Nokia Symbian etc, enabling you to watch from anywhere.*

Key Features

- Mobile Phone compatible
- H.264 Compression
- Built in DVD Writer
- Mouse or IR Remote Control
- Audio 4 In 2 Out
- Simultaneous Live Playback
- * Download of application required

- Easy Backup DVD or USB or Network
- BNC or VGA Main Monitor Out
- BNC Spot Monitor Out
- Alarms
- Various HDD sizes available



6-8 Garrick Industrial Centre, Irving Way, Iondon NW9 6AQ, England tel: technical support +44 (0)20 8732 3350 +44 (0)20 8732 3332 fax: +44 (0)20 8202 3387 www.cbceurope.com






C-MPH16-II

16 Channel H.264 Network DVR with DVD Writer

Specifications



| Description / Model | C-MPH16-II | Web Interface | Internet Explorer, Mozilla Firefox or Google Chrome web browser / QuickTime |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------|--------------------------------------------------------------------------------|
| Video System | NTSC / PAL (auto detection) | | player (10 users access simultaneously) |
| Video Compression Format | H.264 | | *Operating System: Windows 7 / Vista / XP / 2000 |
| Video Input | 16 channels (Composite video signal 1 Vp-p 75Ω BNC) | Network Protocol | TCP/IP, PPPOE, DHCP and DDNS |
| Video Loop Output | 16 channels (Composite video signal 1 Vp-p 75 Ω BNC) | Remote Independent Operation | YES |
| Video Output (BNC) | Main Monitor: Main monitor out | Event Notification | By FTP & E-Mail |
| | Call Monitor: For sequence display | R.E.T.R. (Remote Event Trigger | YES |
| Video Output (VGA) | Built-in VGA interface for LCD monitor for Main monitor out. VGA & Main BNC output are same output) | Recording) | |
| | | IR Remote Control | YES (IR receiver built-in) |
| Audio Input / Output | 4 audio inputs, 2 audio output (Mono) | Mobile Surveillance | YES (Including iPhone, BlackBerry, WinCE, J2ME & Android) |
| Maximum Recording Rate | | Picture Zoom | 2X digital zoom |
| Frame | 704×480 pixels with 120 IPS <ntsc></ntsc> | PTZ Control | YES |
| | 704×576 pixels with 100 IPS <pal></pal> | Alarm Input / Output | 16 inputs, 1 output |
| Field | 704x240 pixels with 240 IPS <ntsc> 704x288 pixels with 200 IPS <pal></pal></ntsc> | Key Lock (Password Protection) | YES |
| CIF | 352×240 pixels with 480 IPS <ntsc></ntsc> | User Level | Administrator & Operator |
| | 352×288 pixels with 400 IPS <pal></pal> | Video Loss Detection | YES |
| Image Quality Setting | SUPER BEST / BEST / HIGH / NORMAL | Camera Title | Supports up to 6 letters |
| Hard Disk Storage | Accommodates 2 SATA HDDs (1 HDD capacity up to 2TB) | Video Adjustable | Hue / Saturation / Contrast / Brightness |
| Quick Search | Time / Motion / Alarm search mode | Date Display Format | YY/MM/DD, DD/MM/YY & MM/DD/YY |
| SATA Interface | Built-in | Daylight Saving | YES |
| Recording Mode | Manual / Timer / Motion / Alarm / Remote | Power Source (±10%) | DC 19V |
| Multiplex Operation | Live display / record / playback / backup / | Power Consumption (±10%) | < 64 W |
| | network operations | Operating Temperature | 10°C ~ 40°C(50°F~104°F) |
| USB Mouse Control | YES | Dimensions (mm)** | $432(W) \times 90(H) \times 326(D)$ |
| Motion Detection Area | 16×12 grids per channel | System Recovery | System auto recovery after power failure |
| Motion Detection Sensitivity | 3 adjustable parameters for accurate | Optional Peripherals | Keyboard Controller |
| | detection | WARRANTY | |
| Pre-alarm Recording | YES | Warranty Period | 3 Years |
| Backup Device | DVD Writer / USB 2.0 flash drive / Network | | |
| Web Transmitting Compression Format | H.264 | | |
| Ethernet | 10/100 Base-T. Supports remote control and live view via Ethernet | | |





V1.01