


ZC-F/Y SERIES





Features

- Excellent Picture Quality
- High Sensitivity With Latest 1/3" CCD
- Impressive Colour Reproduction
- Outstanding BLC Function
- Easy Setting
- Accepts DC Or Video Type Auto-Iris Lens
- Line Lockable With Line Phase Adjustment



Appearance



Specifications / ZC-F/Y Series

Model No.	ZC-F11C3	ZC-F11C4	ZC-F11CH3	ZC-F11CH4	ZC-Y11P3	ZC-Y11P4	ZC-Y11PH3	ZC-Y11PH4
TV System	CCIR				PAL			
Lens Mount	CS Mount							
Scanning System	2 : 1 Interlace							
Image Sensor	1 / 3 Inches IT. CCD							
Effective Elements (H) x (V)	500 x 582		752 x 582		500 x 582		752 x 582	
Video Outputs	1.0V(p-p) / 75Ω							
Resolution (Horizontal)	380TVL		570TVL		330TVL		480TVL	
Min. Illuminance	Less Than 0.09Lux (F1.2 / 50IRE) Less Than 0.04Lux (F0.8 / 50IRE)		Less Than 0.18Lux (F1.2 / 50IRE) Less Than 0.08Lux (F0.8 / 50IRE)		Less Than 0.6Lux (F1.2 / 50IRE) Less Than 0.27Lux (F0.8 / 50IRE)		Less Than 1.2Lux (F1.2 / 50IRE) Less Than 0.54Lux (F0.8 / 50IRE)	
S/N Ratio	More Than 50dB							
γ Characteristics	0.45							
Sync. System	INT. / L.L. (Manual Switch)							
Iris Control	Video Iris : Power DC 12V, Less Than 50mA							
	Video Signal : 0.7V(p-p) (High Impedance)							
	DC Iris : Shutter Speed 1/50 Sec. Fixed							
White Balance	AES : 1/50~1/100,000 Sec.				AES : 1/50~20,000 Sec.			
	Auto Tracking White Balance							
Power Supply	AC230V ±10% (50Hz ±1%)	AC24V ±10% (50Hz ±1%) DC12V ±10%	AC230V ±10% (50Hz ±1%)	AC24V ±10% (50Hz ±1%) DC12V ±10%	AC230V ±10% (50Hz ±1%)	AC24V ±10% (50Hz ±1%) DC12V ±10%	AC230V ±10% (50Hz ±1%)	AC24V ±10% (50Hz ±1%) DC12V ±10%
Power Consumption	Less Than 4W	Less Than 3W	Less Than 4W	Less Than 3W	Less Than 4.5W	Less Than 3.5W	Less Than 4.5W	Less Than 3.5W
Ambient Temperature	Operation : -10°C ~ +50°C Storage : -20°C ~ +60°C							
Ambient Humidity	Operation : RH80% Max. (Keep Free From DAMP) Storage : RH90% Max. (Keep free From DAMP)							
External Dimensions	60(W) x 46(H) x 95(D)mm							
Weight	Less Than 600g	Less Than 300g	Less Than 600g	Less Than 300g	Less Than 600g	Less Than 300g	Less Than 600g	Less Than 300g
Input & Output	Video Output : BNC							
	Euro Plug With 2 Meters Cable	Screwless 2 Pins Terminal	Euro Plug With 2 Meters Cable	Screwless 2 Pins Terminal	Euro Plug With 2 Meters Cable	Screwless 2 Pins Terminal	Euro Plug With 2 Meters Cable	Screwless 2 Pins Terminal
Switches	Iris Control : Video / AES / DC							
	Sync. System : INT. / L.L. BLC : ON / OFF							
Up/Down Buttons	Line Lock Phase Adjustment (L.L. Mode)							
Volume	DC Iris Level Adjustment (Effect Only When DC Iris)							
Standards	CE Standards, CE Compliance (Self-Declaration)							

Features and specifications are subjected to change without any notice for further improvement.



CBC GROUP

<http://www.cbc.co.jp>

Tokyo Osaka Nagoya Fukuoka Kanazawa Sendai New York Los Angeles London Milan Paris Düsseldorf Warszawa Hong Kong Taipei Jakarta Bangkok Singapore Shanghai Beijing Bangladesh