


DISCREET CAMERA

COLOUR

SM-650/A

Surface Mount colour camera





- Wall or ceiling mountable
- Camera mounted on manually adjustable miniature 'swivel and tilt' cradle, for exact camera positioning
- Smoked face plate disguises exact lens direction
- Ideal for mounting at head height by doorways to monitor the movement of people through buildings



1/4" CCD



350 TV lines



5.0 lux sensitivity



Supply voltage: 12 Vdc



Audio output: 1V p-p

Lens option Lens **Product Code** 4.0mm SM-650/A

- Cables feed directly into wall or ceiling so cannot be tampered with
- Comes with free power supply
- Comes with free audio capability
- Comes with lint-free cleaning cloth to remove grease and dirt from case and lens

See Also:



SM-350/A Monochrome option



IW-350/A Monochrome inwall camera



IW-650/A Colour in-wall camera

	Ī
	F
	L
E 0	E
Π	S
	Ī
	S

	ŀ
	L
E0	E
₫	S
>	_
	-

	I
	-
	H
	-
	L
	-
<u> </u>	E
•••	-
	-
	5
-	
	-
	١
	_
	5
	2
	_

	I
	ŀ
	ī
EO	E
VIDEO	-
>	_
	1

	SPECIFICATION	MOD-607 camera module
	Image sensor	1/4" CCD sensor, 500 (H) x 582 (V) pixels
	Horizontal resolution	350 TV lines or greater
	Lens options	SEE TABLE
EO	Electronic shutter	Automatic linear shutter
M	Sensitivity	5.0 lux
	Video output	PAL, 1Vp-p, 75 Ohms
	Supply voltage	12 Vdc <u>+</u> 10%
	Working temperature	-5°C to +40°C

0	
=	
J	

_	· · · · · · · · · · · · · · · · · · ·	Omni-directional electret
3	Audio output	1Vp-p, 600 Ohms
∢	Audio bandwidth	100Hz - 10KHz, +/- 3dB

Specification and availability of products are subject to change without notice