

TECHNICAL DATA SHEET

GTA016

Channel Active Video Receiver



KEY FEATURES

- 16 Channel 19-inch 1U Rack Mounting Hub
- Active Receiver Unit with Individual Gain Adjustments
- Transmission up to 1.4Km in Colour, 2.4Km in Monochrome
- 16-Way Terminal Block for Video Input
- 16 x BNC Connector for Video Output
- Built-In Transient Protection and Ground Lifting
- For Use with Category 5, 5e or 6 UTP Cable
- Supplied with 12V DC Power Supply

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	GTA016
Power	12V DC Max 400mA
Nominal Input Impedance	100-105 Ohm (Balanced)
Nominal Output Impedance	75 Ohm (Unbalanced)
Input Connector	16 Position Terminal Block
Output Connector	16 x BNCCconnector
Video Input	1V p-p
Video Output	1V p-p
Cable Type	Category 5 5e or 6 UTP (24AWG)
EMI Standard	Meets FCCClass B /CE
Dimensions (W x H x D)	482mm x 44mm x 170mm
Material	Metal Black inColour
Operating Temperature	0° C ~ +40° C
Operating Humidity	20% ~ 80%

Features and specification are subject to change for further improvement without any notice.