



Reader (PR400)

The New Geoffrey[™] PR400 Series Proximity & Smart reader range takes RF/ID technology to the ultimate in sophistication, customer acceptance, and cost effectiveness. The PR400 readers are quick and easy to install and have been designed for the most demanding access control applications. One of the most unique features of the PR400 series is the ability to offer custom branded technology & housings with company names, logos and colors. A choice of body and cap colors is also available to suit corporate styles.

FEATURES

• Cards and Tags A wide range of identity cards and key fobs are available to suit virtually every application. Standard ISO style plastic cards, with or without magnetic stripe, can be surface printed using standard PVC card printers

• Environmental

The PR400 series is suitable for both indoor and outdoor use. The readers will operate reliably in harsh environments with temperature -20° C to $+60^{\circ}$ C

• Quick and Easy to Install

Surface fixing design with stainless steel fixings supplied. May be fixed flush to metal surfaces with no significant loss of range. Specially moulded covers are provided to hide the fixing screws

Flexible Connection

Two visual indicators and an integral beeper allow for various connection combinations. The beeper and one LED can be controlled externally giving complete flexibility for control applications

Multi Technology Cards

ISO PVC cards are available with a Hi-Co magnetic stripe plus smart chip for multi-function applications. Also allows backward compatibility with installed magnetic stripe readers

SPECFICATION

- Read Range
 ProxCard® II Card 18 cm
 ISOProx® Card 12 cm
 ProxKey™ Keyfob 4 cm ProxCard®
 Plus Card® 6 cm
 Smart Mifare® Card 3 cm
 Smart LEGIC® Card 5 cm
- Mechanical (Housing) Moulded polycarbonate with fully encapsulated Electronics Size: 108mm×52mm×22mm Weight: 115g nominal Mounting: 2X M3.5 screws (supplied)
- Connection
 - 1. 5 to 16 VDC
 - 2. Clock / Data 1
 - 3. Data / Data 0
 - 4. Green LED
 - 5. Red LED
 - 6. Card present
 - 7. Supply 0V

- Input power 5 -16 VDC
- Current 120 mA typical
- Data Voltage Rest >4VDC, Active <1VDC
- Data Output Wiegand Format Magnetic Stripe Customized
- Indication
 Red LED power
 Green LED card read
 Buzzer audible indicator
- Environmental Operating Temp-20°C to +60°C Humidity: 100% RHNC

Part Number

GPR402-G34 Geoffrey[™] Proximity Formats

GPR430 HID® Proximity Formats

GPR470

Smart LEGIC[®] Contactless Technology

GPR480 Smart Mifare® Contactless Technology

Geoffrey

Geoffrey Industries (UK) Ltd Amberwell House, Pottersheath Rd Welwyn, Hertfordshire, AL6 9SY Phone +44 (0) 1438 817000 Facsimile +44 (0) 1438 814344 e-mail: info@geoffrey.co.uk Web Site, www.geoffrey.co.uk