

# Geoffrey

## *Sophisticated Reader PR500 Series™*



*Reader (PR500)*

The New Geoffrey™ PR500 Series Proximity & Smart Keypad reader takes RF/ID technology to the ultimate in sophistication, customer acceptance, and cost effectiveness. The PR500 series reader is quick and easy to install and have been designed for the most demanding access control applications. The PR500 are available with custom branded housings with company names, logos and colors.

### **FEATURES**

- **Cards and Tags**  
A wide range of identity cards and key fobs are available to suit virtually every application. Standard ISO style plastic cards, with or without magnetic stripe, can be surface printed using standard PVC card printers
- **Environmental**  
The PR500 series is suitable for both indoor and outdoor use. The readers will operate reliably in harsh environments with temperatures from -20 °C to +60 °C

- **Keypad Data**  
Keypad data is transmitted on the data lines in industry standard formats
- **Quick and Easy to Install**  
Surface fixing design with stainless steel fixings supplied. May be fixed flush to metal surfaces with no significant loss of range
- **Flexible Connection**  
Two visual indicators and an integral beeper allow for various connection combinations. The beeper and one LED can be controlled externally giving complete flexibility for control applications
- **Multi Technology Cards**  
ISO PVC cards are available with a Hi-Co magnetic stripe for multi-function applications. Also allows backward compatibility with installed magnetic stripe readers
- **Input power**  
5 –16 VDC
- **Current**  
120 mA typical
- **Data Voltage**  
Rest >4VDC, Active <1VDC
- **Data Output**  
Wiegand Format 26-34bit  
Customized output also available to special order
- **Indication**  
Red LED - power  
Green LED - card read  
Buzzer - audible indicator
- **Environmental**  
Operating Temp:-20°C to +60°C  
Humidity: 100% RHNC

## SPECIFICATION

- **Read Range**  
ISOProx™ Card 22 cm  
SmartProx™ Card – 12 cm  
Smart Mifare® Card – 3 cm  
Smart LEGIC® Card – 5 cm
- **Mechanical (Housing)**  
Moulded polycarbonate with fully encapsulated Electronics  
Size: 108mm×82mm×28mm  
Weight: 203g nominal  
Mounting: 2X M3.5 screws (supplied)
- **Connection**
  1. 5 to 16 VDC
  2. Clock / Data 1
  3. Data / Data 0
  4. Green LED
  5. Red LED
  6. Card present
  7. Supply 0V

## Part Number

- GPR500-G34**  
Geoffrey™ Proximity Formats
- GPR530**  
HID® Proximity Formats
- GPR570**  
Smart LEGIC® Contactless Technology
- GPR580**  
Smart Mifare® Contactless Technology

# Geoffrey

Geoffrey Industries (UK) Ltd  
Amberwell House, Pottersheath Rd  
Welwyn, Hertfordshire, AL6 9SY  
Phone +44 (0) 1438 817000  
Facsimile +44 (0) 1438 814344  
e-mail: info@geoffrey.co.uk  
Web Site, www.geoffrey.co.uk