

## GVT-17P / GVT-19P

Professional 17" and 19" TFT-Displays  
with metal sheet housing

### Product information

Both TFT-Monitors combine highest functionality and excellent design together for use in professional CCTV applications. Thanks to their wide viewing angles, a good contrast ratio and a high resolution in combination with maximum switchover times of 1 - 2 s for video signals, their technical specifications meet the highest demands for security applications. They offer a space saving alternative for standard video monitors and can be mounted in accordance to the VESA-Standard or can be placed on a desktop via the base stand providing concealed cable ducting. While automatic switching between PAL and NTSC is supported, the external wide range power supply unit prepare the monitors at its best for international applications.



- Brilliant picture quality
- Supports video and VGA-signals
- Wide viewing angles
- Fast response times
- Suitable for video surveillance systems
- Mountable in accordance with the VESA standard
- Metal housing with concealed cable routing

## Technical data

|                                            | <b>GVT-17P</b>                                                                                        | <b>GVT-19P</b>                 |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------|--------------------------------|
| Format                                     | 17" (43 cm)                                                                                           | 19" (48 cm)                    |
| Resolution                                 | 1280 x 1024 Pixel, VGA up to SXGA                                                                     |                                |
| Video standard                             | PAL / NTSC, automatic                                                                                 |                                |
| Inputs                                     | 1 x composite video (BNC-Socket)<br>1 x PC-input (DVI-I)                                              |                                |
| Luminance                                  | 300 cd/m <sup>2</sup>                                                                                 |                                |
| Contrast ratio                             | 500:1                                                                                                 | 1000:1                         |
| Viewing angle                              | 140° horizontal, 130° vertical                                                                        | 178° horizontal, 178° vertical |
| Response time                              | 8 ms                                                                                                  |                                |
| Color depth                                | 16.2 Mio colors<br>(6-bit + FRC for RGB)                                                              | 16,700,000 colors              |
| Switchover/Lock on times for video signals | Switchover time for unsync. video signals: < 1 s<br>Lock on times for video signals from sleep: < 2 s |                                |
| Housing                                    | Metal sheet housing, VESA-Standard mounting possible                                                  |                                |
| Design                                     | Functional product design with base stand and concealed cable feeding                                 |                                |
| Voltage supply                             | 100 - 240 V AC, 50 / 60 Hz                                                                            |                                |
| Power output of PSU                        | 50 W                                                                                                  |                                |
| Dimensions in mm (W x H x D)               | 375 x 380 x 140                                                                                       | 425 x 395 x 175                |
| Weight                                     | 6.5 kg                                                                                                | 7.0 kg                         |
| Operating temperature                      | 0 °C - 40 °C                                                                                          |                                |
| Accessories                                | External PSU and base stand<br>DVI-I / VGA-Adapter (D-Sub, 15 Pin)                                    |                                |
| <b>Order No.</b>                           | <b>5.35310</b>                                                                                        | <b>5.35315</b>                 |

GVT-17-P\_GVT19-P\_EN\_7.75631 24.10.2007

Technical alterations reserved

**GEUTEBRÜCK GmbH** · Im Nassen 7-9 · D-53578 Windhagen · Tel. +49 (0)2645 137-0 · Fax-999

E-mail: [info@geutebrueck.com](mailto:info@geutebrueck.com) · Web: [www.geutebrueck.de](http://www.geutebrueck.de)



Networking Infrastructure Solutions