

VIPCAM-GNSD671

Remote-controllable extremely high-resolution
1/4" Day/Night dome



Product information

The GEUTEBRÜCK VIPCAM-GNSD671 is a new compact high speed dome camera system designed to deliver superb performance and durability with an unobtrusive housing that looks good in any security and surveillance installation. It is especially designed for indoor conditions and can easily be adapted with optional accessories to fit well under various mounting situations. This extremely compact and lightweight dome camera delivers a superb image quality, containing a new generation of an advanced DSP color camera with 23x optical and 12x digital zoom.

- | 23x motor-zoom lens (3.6 - 82.8 mm)
- | Wide dynamic range
- | Text insertion depending on position
- | 8 privacy zones [in independent viewing areas] (Privacy masking)
- | High pan/tilt speed with presets (up to 400°/s with 0,225° preset accuracy)
- | Supports 25 pictures/s in QCIF, CIF, 2CIF and 4CIF at all quality levels of compression
- | Usage of existing network structures
- | Vandalism-proof hood out of polycarbonate

GEUTEBRÜCK

Competence in Video Security

Technical data

Image sensor (Chip)	1/4" Sony CCD sensor
Scanning system	2 : 1 Interlace
Scanning frequency	15.625 kHz (H), 50 Hz (V)
Pixel (H x V)	752 x 582 (effective)
Horizontal resolution	540 TVL
Minimum sensitivity:	
Color	0.1 lux (50 IRE) IR cut filter, AGC on
B/W	0.01 lux (50 IRE) IR pass filter, AGC on
Synchronization	Internal / External (line lock)
S/N ratio	>49 dB (AGC off)
White balance	Automatic / Manual
Shutter	On / Off - Manual/Automatic electronic (AES), 1/1.5 to 1/4000 s
Back-light compensation	On / Off
Automatic gain control (AGC)	Automatic / Manual
Extendend dynamic range	Yes
LAN interface	RJ45 connector, 10/100Base-TX
Transmission	TCP (Transmission Control Protocol)
Compression/Encoding	Pictures directly will be transmitted in a GeViScope compatible data format: MPEG4CCTV
Color / B/W switching	Automatic (IR-cut filter)
Privacy masking	8 zones, Auto Pan: 4, Tours: 4
Lens	3.6 mm to 82.8 mm (optical)
Zoom ratio (optical)	23x
Zoom ratio (digital)	1x - 12x proportional
Panning range	360° endless
Tilting range	-10° to 190°
Panning/Tilting speed	1°/s to 90°/s (manual)
Preset speed	5°/s to 400°/s (pan/tilt)
Preset accuracy	0.225° (pan), 0.45° (tilt)
Auto flip / Digital flip	Yes
Auto focus	Automatic / Manual
Preset positions	256 positions with with freeze function
Inbuilt protocols	JVC/GEUTEBRUECK protocol
Operating temperature	- 10 °C to + 45 °C (0 °C bis 40 °C recommended)
Humidity in operation	0 % to 90 % rel. humidity (non condensing)
Protective rating	IP 20 (for indoor use only)
Voltage supply	24 V AC
Power consumption	Approx. 20 W
Dimensions in mm (Diameter x H)	131 x 226
Weight	Approx. 1.6 kg
Certificates	CE, FCC
Order No.	0.34870

Technical alterations reserved

GEUTEBRÜCK GmbH

Im Nassen 7-9 | D-53578 Windhagen | Tel. +49 (0)2645 137-0 | Fax-999 E-mail: info@geutebrueck.com | Web: www.geutebrueck.de