

SSG-401/2, WSG-401/3, WSG-401/3DK, WSG-421/3

Compact weather- and dustproof housing



Product information

- | Excellent price/performance ratio for 230 VAC cameras
- | Aluminium case with V2A stainless-steel screws
- | Internal camera mounting-height adjustment
- | Temperature regulation via PTC heating element and additional safety thermostat
- | Isolated camera mounting to avoid ground-loops
- | VDE approved construction
- | IP-66 protection rating
- | TÜV approved safety (German safety standards authority)

GEUTEBRÜCK

Competence in Video Security

Technical data

	SSG-401/2	WSG-401/3	WSG-401/3DK	WSG-421/3
Description	Dustproof housing without sun-shield, heater or safety thermostat	Weatherproof housing with sun-shield, self-regulating heater and safety thermostat	Weatherproof housing with sun-shield, self-regulating heater, integrated power connection board and safety thermostat	Weather proof housing with sun-shield, self-regulating heater, integrated power connection board and safety thermostat
Folding down	YES			
Concealed cable access	NO			YES
Finish	RAL 7032			
Case	Aluminium			
Heater supply	NO	230 VAC		
Cable access	3 x PG-9 cable glands			4 cable glands- (12 mm in diameter/ concealed access)
Outer dimensions	Approx. 109 x 98 x 410 mm (W x H x D)			Approx. 109 x 98 x 430 mm (W x H x D)
Usable internal size	80 x 75 x 300 mm (W x H x D)			
Protection rating	IP 66			
Weight	1,8 kg	2,6 kg	Approx.3 kg	4,7 kg
Order No.	5.15741	5.15752	5.15756	5.15761

Accessories

Type	WK-400	Ceiling mount incl.	Wall mount bracket incl.
Description	Adjustable, wall-mounting bracket with locking screw, RAL 7032 (pebble grey)	Ceiling mount bracket with locking screw, RAL 7032 (pebble grey)	Adjustable wall mount bracket with concealed cable access and locking screw, RAL 7032 (pebble grey)
Order No.	5.18680	-	-
Type	MK-300	-	MAK-W
Description	Mast console	-	Mast mount adapter for the WSG-421
Order No.	5.18370	-	5.18371
Type	-	-	NT/AC-400 mains unit
Description	-	-	230 VAC / 24 VAC, 400 mA
Order No.	-	-	5.03595
Type	NT/DC-1500 mains unit		
Description	230 VAC / 12 VDC, 1500 mA		
Order No.	5.03630		

Technical alterations reserved

GEUTEBRÜCK GmbH

Im Nassen 7-9 | D-53578 Windhagen | Tel. +49 (0)2645 137-0 | Fax-999 E-mail: info@geutebrueck.com | Web: www.geutebrueck.de