

## WSG-500 Series

### Camera Housings



- IP-66 protection rating
- Aluminium case with V2A stainless-steel screws
- Available with concealed cable access or 3 x cable glands
- Internal camera mounting-height adjustment
- Self-regulating PTC heating element
- Isolated camera mounting to avoid ground-loops
- VDE approved construction  
(association of German electrical engineers)
- TÜV approved safety (German safety standards authority)

Technical data		
	WSG-501	WSG-521
Description	Weather-proof housing with sun shield, self-regulating heater and safety-thermostat	
Cable access	3 x PG-9 cable glands	Concealed access
Finish	Powder coated, pebble grey, RAL 7032	
Material	Aluminium	
Heater supply	230 VAC	
Outer dimensions	135 x 116 x 445 mm (w x h x d)	
Usable internal size	320 mm	
Protection rating	IP 66	
Weight	2.9 kg	5.0 kg
<b>Order part number</b>	<b>5.15780</b>	<b>5.15770</b>
Accessories		
Type	WK-500	MAK-W
Description	Adjustable, wall-mounting bracket with locking screw RAL 7032 (pebble grey)	Pole-mounting adapter for WSG-421/521 housings material: high-tensile steel fastening: stainless-steel bands
<b>Order number</b>	<b>5.18690</b>	<b>5.18371</b>

Technical alterations reserved.