

≈ PWR-12DC-4-5

FC

4 Camera 12VDC 5Amp Power Supply



The PWR-12DC-4-5 is a CCTV power center engineered to manage remote camera and accessory power requirements. The PWR-12DC-4-5 distribution module is designed with 4 individually fused outputs for powering up to 4 CCTV cameras and accessories. It will provide 12 VDC via distribution to four fused outputs with a total of 5 Amps continuous supply current. The PWR-12DC-4-5 power center is housed in a premium lockable heavy gauge metal enclosure.

Key Features


- Convenient screw and terminal and fuse access
- AC power LED indicator
- Includes transformer and spare fuses
- Multiple knockouts to accommodate various wiring configurations
- Uses easy to find automotive style fuses

Technical Specifications

PWR-12DC-4-5

FEATURES		
Convenient screw and terminal and fuse access		
Separation panel between transformers and output access		
Power ON/OFF switch		
Individual LED's for each fused output		
AC power LED indicator		
Double coated polyurethane finish		
Multiple knockouts to accommodate various wiring configurations		
Uses easy to find automotive style fuses		
Includes transformer and spare fuses		
Built-in battery charger		
Lockable heavy gauge metal enclosure		

Dimensions	Ų	Jnit : mm (inch)
Dimensions		



SPECIFICATIONS		
Input	115VAC 50/60 HZ; 1.0 Amps	
Output	3 Amps	
5 Amps 100VA supply currents at 70°F		
Fuse	5 Amps	
Four 12VDC individually fused outputs		
Transformers	110/28VAC, 100VA	
Enclosure Dimensions	254 x 228.6 x 114.3mm (10" x 9" x 4.5")	