





FEATURES

- 16 Channel video D1 400fps recording capability
- Built-in DVD-RW for backup
- High Picture Quality: MPEG4, D1(704x576)
- Control possible by mouse (USB) or keyboards (RS485)
- HDMI output possible resolution 1080P
- Remote monitoring and control through network (LAN)
- Various recording features (Normal, schedule, motion, alarm)
- USB2.0 Interface: USB Memory/ USB external HDD/ CD-RW, external DVD-RW backup
- Compatible to French law for quality in CCTV applications



Design and specifications are subject to change without notice

Status 07/2008

Tel.: +49(0)211 2470 16-0 Fax: +49(0)211 24701611



CDE	$C \Lambda T$	IONS	

Operating System	Embedded OS		
Basic Internal Storage	500 GB		
Internal Storage Max. Expansion	Internal (500 GB x 5), ESATA (500 GB x 8)		
External Backup	USB HDD, USB Memory, DVD-ROM, Network		
Internal Backup	Built in DVD-RW drive		
Video Inputs	16 CH Composite, BNC, Looped		
Video Outputs	5 CVBS (1 Main, 4 Spot), 1 HDMI (1080P), 1 VGA (1280x1024)		
Video Compression	MPEG4		
Display Speed	400 fps		
Display Resolution	704x576, 704x288, 352x288		
Recording Mode	Continuous, Event Alarm, Motion, Video Loss, Schedule		
Recording Speed	400fps (352x288), 400fps (704x288), 400fps (704x576)		
Recording Resolution	CIF(352x288), Half D1(704x288), Full D1(704x576)		
Search Mode	Date/Time, Event Alarm, Motion, Video Loss, Go First, Go Last, Search Backup		
Audio Inputs	16 CH (4 RCA, 12 D-sub)		
Audio Outputs	1 CH, RCA, -6dBm		
Alarm Inputs	16		
Alarm Outputs	4		
Motion Detection	On/Off/Area Setting		
Network	Ethernet, 10/100 BaseT, ADSL Static IP, ADSL Dynamic IP(PPPoE),Cable Network (Dynamic IP)		
Client software	Net-i (Windows 2000, XP, Vista), Web Viewer (Internet explorer)		
Control	1 port RS485 and Mouse (USB)		
Time Setting	Setting by NTP Server local or internet		
Serial Interface(s)	RS-485, PTZ Device control, System Keyboard, USB mouse		
Serial Interface(s)	1 SVGA screen port, 1 parallel port, 1 serial port, 6 USB2.0 ports, 1 Ethernet port		
Multiplex Function	Triplex		
Auto Switching	0, 3, 5, 10, 20, 30 sec		
Supply Voltage	220 ~ 240 VAC/50Hz		
Power Consumption	75 W		
Weight	7.8 kg		
Dimensions w*h*d	440 x 88 x 430 mm		






Design and specifications are subject to change without notice

Status 07/2008

Max-Planck-Straße 15a-c D - 40699 Erkrath Tel.: +49(0)211 2470 16-0 Fax: +49(0)211 24701611



DIMENSIONS






FRONT & REAR VIEW






NET-I Software



250 DVR Support
Remote View Live & Play back
Search On Camera /Data / Time / Alarms
Control P/TZ Cameras
Export Clips to Local PC
Remote Administration



Status 07/2008



security

AASSET Security GmbH

Max-Planck-Straße 15a-c D - 40699 Erkrath Tel.: +49(0)211 2470 16-0 Fax: +49(0)211 24701611



Web viewer (internet explorer)





Remote View Live & Play back Search On Camera /Data / Time / Alarms Control P/TZ Cameras Export Clips to Local PC Remote Administration



Design and specifications are subject to change without notice

Status 07/2008

Max-Planck-Straße 15a-c D - 40699 Erkrath Tel.: +49(0)211 2470 16-0 Fax: +49(0)211 24701611