


4 Channel High Resolution Compact DVR

SVR-480




Specifications


| | | SVR-480 | |
|-------------------------|---|--|---|
| DISPLAY | Video | Inputs 4 Composite video 1 Vpp, 75 ohm automatic termination | |
| | Resolution | NTSC : 704 x 480 | PAL : 704 x 576 |
| | Frame Rate | NTSC : 120fps | PAL : 100fps |
| Live | Resolution | NTSC : 704 x 480 | PAL : 704 x 576 |
| | Multi Screen Display | 1 / 4 | |
| PERFORMANCE | Compression | MPEG-4 | |
| | Record Rate | NTSC Up to 120fps@704 x 480 (4CIF) Up to 120fps@704 x 240 (2CIF) Up to 120fps@352 x 240 (CIF) | PAL Up to 100fps@704 x 576 (4CIF) Up to 100fps@704 x 288 (2CIF) Up to 100fps@352 x 288 (CIF) |
| | Mode | Manual, Schedule, Event | |
| | Overwrite Modes | Continuous | |
| Recording | Pre-alarm | Up to 5 sec. | |
| | Post-alarm | Up to 60 sec. | |
| | Search Mode | Date/Time, Event, Calendar, Thumbnail, Text (SNM-128S) | |
| | Playback Function | REW, FWD, Frame advance | |
| Search & Playback | Transmission Speed | Up to 16Mbps | |
| | Bandwidth Control | Automatic | |
| | Multi Stream | MPEG-4 / JPEG | |
| | Max. Remote Users | 10 Simultaneously | |
| Network | Protocol Support | TCP/IP, ARP, ICMP, DHCP, PPPoE, UDP, SMTP, SNMP, FTP, SNT, HTTP, DNS, DDNS, NTP | |
| | Monitoring | CMS Software (SVM-S1, SNM-128S/P), Web viewer | |
| | Maximum Capacity | Up to 6TB using external storage option | |
| | Internal HDD | Up to 2 SATA HDDs | |
| Storage | External HDD | Up to 1 expansion bay | |
| | DVD Writer (Back up) | DVD-R / CD-R | |
| | USB (Back up) | 2 External USB Ports | |
| | File Format (Back up) | BMP, AVI, Proprietary format (Include viewer) / JPEG (Exclusive viewer) | |
| Security | Password Protection | 1 Admin, 10 User | |
| | Data Authentication | Watermark | |
| INTERFACE | | | |
| Monitors | VGA | Analog RGB 800 x 600, 1024 x 768, 1280 x 1024 resolution | |
| | Main Composite | BNC, 1 Vp-p, 75 ohm, Multi-screen, Menu, Playback | |
| | Sub Composite | 1 BNC, 1 Vp-p, 75 ohm | |
| | Loop Outputs | 4 Composite video 1 Vpp, 75 ohm | |
| Audio | Inputs | 4 Line in, 30K ohm | |
| | Output | 1 Line, 100K ohm | |
| | Compression | ADPCM | |
| | Sampling Rate | 16KHz | |
| Alarm | Inputs | Terminal 4 inputs, NO/NC | |
| | Outputs | Terminal 2 relay outputs | |
| | Remote Notification | Notification via e-mail | |
| | Ethernet | RJ-45 10/100 Base-T | |
| Connections | Serial Interface | RS-232C | |
| | PTZ Control Interface | RS-485 | |
| | PTZ Keyboard | RS-485, Max. signal voltage ±12V | |
| | USB | 2 USB 2.0 ports | |
| Communication Protocols | eSATA | 1 External SATA port | |
| | Application Support | ATM/POS, Remote controller | |
| GENERAL | | | |
| Electrical | Input Voltage | 100 ~ 240V AC ±10%, 50/60Hz, Auto ranging | |
| | Power Consumption | Max. 45W (With 1X HDD) / Max. 60W (With 2X HDD) | |
| Environmental | Operating Temperature | +5°C ~ +40°C (+32°F ~ +104°F) | |
| | Operating Humidity | 0% ~ 60%RH | |
| Mechanical | Dimensions (WxHxD) | 350 x 88 x 401.3mm (13.77" x 3.46" x 15.8") | |
| | Weight (4X Hard Disks) | Approx. 5.6Kg (12.35 lb) | |
| Language | Rack Mount Kit | N/A | |
| | Supported PTZ Cameras | Samsung Techwin, Pelco D, Pelco P, Panasonic, Bosch, SEC, AD | |
| Certifications | English, Spanish, French, German, Italian, Portuguese, Polish, Russian, Turkish, Japanese, Czech, Serbian, Swedish, Rumanian, Danish, Korean FCC (Class A), CE (Class A) | | |

Dimensions

Unit : mm (inch)



Rear panel



Design and specifications are subject to change without notice.



High Resolution,
High Performance
4 Channel DVR



SVR-480

4 Channel High Resolution Compact DVR

- 4 CIF resolution & 120fps max recording speed
- Proprietary MPEG-4 compression & JPEG streaming support
- DVD back up & 4 channel audio recording
- Provided with powerful centralized management software




SAMSUNG TECHWIN CO., LTD.
145-3, Sangdaewon 1-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do Korea 462-703
Tel : +82-31-740-8151-8 Fax : +82-31-740-8145
www.samsungipolis.com

SAMSUNG TECHWIN AMERICA Inc.
1480 Charles Willard St, Carson, CA 90746, UNITED STATES
Tel Free : +1-877-213-1222 Fax : +1-310-632-2195
www.samsungcctvusa.com

SAMSUNG TECHWIN EUROPE CO., LTD.
Samsung House, 1000 Hillwood Drive, Hillwood Business Park
Chertsey, Surrey, UNITED KINGDOM KT16 0PS
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325

TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONICS CO., LTD.
No. 11 Wei 6 Street, Micro-Electronic Industrial Park
Jingang Road, Tianjin, P.R. CHINA 300385
Tel : +86-22-23887788 Fax : +86-22-23887788

DISTRIBUTED BY



I.E-0909

9-2009

www.samsungcctv.com



Vivid Graphics, Convenient Search Options & High Network Performance




High Resolution, High Performance 4 Channel DVR **SVR-480**

The SVR-480 is an easy to install high performance DVR producing recorded images in real-time at full resolution. It offers dual codec technology to enhance the network performance and video management software to manage multiple DVRs. With the easy to use search and back up option, SVR-480 delivers the essential features in an economical package making it a best solution for small retails, health care, government offices, and casinos.



704 x 480(N) Max Resolution & 120fps(N) Max Recording Speed

The SVR-480 can record MPEG-4 in high resolution images at 30fps per channel, delivering clear, vivid video for accurate monitoring.



Conventional DVR



SVR-480

Convenient Search & Play Options

- **Thumbnail Search**
- Search quickly with video thumbnails.
- **Calendar Search**
- Search by date and time.
- **Bookmark**
- Set convenient video markers to resume playback from there instantly.



Thumbnail Search




Calendar Search

Network Monitoring

Multi-Streaming



A wide selection of video resolutions, screen qualities, and frame rates for real-time monitoring are available to choose from. These options allow network managers to take account of their network traffic.



Centralized Management Software



The SNM-128S/P helps you to centrally manage all our network products including DVRs. This superb software is armed with powerful remote control and monitoring features (SNM-128S supplied as standard).



SNM-128S CMS Software


Default Web Viewer



The self-contained Web Viewer of this DVR enables real-time online monitoring from anywhere, anytime.



Web-viewer Monitor



Web-viewer Playback

Variety of Convenient Options

- **Convenient Control Options**
- Mouse, Remote Controller, Keyboard Controller
- **PTZ Control & Preset Menus**
- **Default DVD & Simple USB Backup Capacity**
- **Supports 4 channel Audio Recording**
- **Easy to Integrate with any ATM/POS System**
- **Multiple Language OSD**
- English, Spanish, French, German, Italian, Polish, Portuguese, Russian, Turkish, Czech, Serbian, Swedish, Rumanian, and Danish.