

WRT-5301

Dual-purpose Wisenet WAVE Network Video Recorder



The WRT-5301 is a dual purpose Wisenet WAVE server and client built into a compact mini-tower form factor. This ready to deploy solution can manage up to 470 Mbps of recording throughput on up to 32TB of storage for a single site, or as an addition to your existing Wisenet WAVE system.

Key Features

- Preloaded and configured with Wisenet WAVE video management system
- Includes (4) four Wisenet WAVE Professional licenses
- 470 Mbps of recording throughput
- Up to 32TB internal storage
- Dual Gigabit Ethernet
- Includes USB mouse and keyboard
- Includes front panel with lock
- Supports Wisenet and ONVIF conformant IP cameras



WRT-5301

SYSTEM		
Video Management Software		Wisenet WAVE
Pre-loaded Licenses		4x Wisenet WAVE Professional license
Recording Bandwidth		470 Mbps
OS Drive Bays		1 x 256GB SSD (internally mounted)
Data Drive Bays		4 x 3.5" (front accessible)
Data Storage		Up to 32TB raw
RAID Support		N/A
Network Interface		2 x RJ-45, Gigabit Ethernet
Processor		Intel Core i5-7500, 3.4GHz
Memory		8GB DDR4
Operating System		Windows 10 IoT Enterprise
Video Outputs		2x HDMI, 1x DVI
USB Ports		4x USB 3.0 (rear), 1x USB 3.0 Type-C (rear), 2x USB 2.0 (front)
Wi-Fi		IEEE 802.11ac
Other Ports		1x PS2, 2x Wi-Fi antennas, 3.5mm audio in/out, 1x SPDIF out
Keyboard & Mouse		Included
MECHANICAL / ELECTRICAL / ENVIRONMENTAL		
Mechanical	Color / Material	Black, Silver / Metal
	Dimensions	7.87" x 10.63" x 12.2" (200mm x 270mm x 310mm)
	Weight	15.4lbs (7kg)
Electrical	Power Supply	250W
	Power Input	100 ~ 240V AC
Environmental	Operating	32°F to 122°F (0°C to 50°C)
	Storage Temperature	-4°F to 176°F (-20°C to 80°C)
	Operating Humidity	5% to 85% RH
Certification		UL, cUL, CB, FCC

* Weight is on chassis without HDDs

* The latest product information / specification can be found at www.hanwhasecurity.com

* Bandwidth performance figures based on performance testing by Hanwha Techwin using Wisenet WAVE

Dimensions

Unit: inch (mm)

