

iCLASS

Clamshell CARD

Value Priced 13.56 MHz Contactless Smart Card
Base Model Numbers: 2080



Application:

HID's *iCLASS*® Clamshell card provides 13.56 MHz read/write contactless smart card technology in a cost effective card package, with an ABS shell construction that provides durability in harsh environments. *iCLASS* provides enhanced security through encryption and mutual authentication while delivering the convenience, affordability and reliability of proximity technology for which HID is known worldwide.

Features:

- 13.56 MHz read/write contactless smart card technology provides high-speed, reliable communications with high data integrity.
- Provides a cost effective way to improve the security of your access control installation.
- Constructed with ABS shell and PVC cover label, offering durable packaging.
- Available in 2k bit (256 Byte), two application area configuration only.
- Provides the HID standard access control application area and one other application area for user customization.
- *iCLASS* technology ensures high security with mutual authentication, encrypted data transfer, and 64-bit diversified keys for read/write capabilities.
- Any existing HID format can be factory or field programmed into the secure HID access control application area.
- Meets ISO 15693 standard for contactless communications.
- A PVC Overlay allows for on-site Photo ID production using most direct image printers.

iCLASS® by

Smart • Powerful • Trusted



iCLASS[®] Clamshell CARD

Value Priced 13.56 MHz Contactless Smart Card



Features

Read/write Functionality for Multi-functional Memory Applications

iCLASS was specifically designed to make access control more powerful, more versatile, and more secure. All radio frequency data transmission between the card and reader is encrypted using a secure algorithm. By using industry standard encryption techniques, iCLASS reduces the risk of compromised data or duplicated cards. For even higher security, the card data may also be protected with DES or triple DES encryption.

Securely separated application areas are each protected by 64-bit diversified read/write keys. Security mechanisms such as mutual authentication and encryption are efficiently combined with fast processing and data communication, resulting in typical transaction times of less than 100 milliseconds.

Proven, Reliable Technology

Offers extremely consistent read range. Unaffected by body shielding or variable environmental conditions, even when close to keys and coins.

Convenient To Use

Can fit into a wallet or purse. Use with a strap and clip as a photo ID badge.

Long Life

Passive, no-battery design allows for an estimated minimum 100,000 reads.

Durability

Strong, flexible, and resistant to cracking and breaking.

Warranty

Lifetime warranty. See complete warranty policy for details.

Base Part Numbers

2k bit (256 Byte) card: 2080

Companion Products

1321 Photo pouch overlay

1324 PVC Direct print overlay

Description

13.56 MHz contactless smart card.

Specifications:

Typical Maximum Read Range*

R10 1.5-2.5" (3.8-6.3 cm)

R30/RW300 1.5-3.0" (3.8-7.6 cm)

R40/RW400 2.5-4.5" (5.1-10.2 cm)

RK40/RWK400 3.0-4.0" (6.3-8.9 cm)

*Dependent upon installation conditions.

Dimensions

2.125" x 3.375" x 0.070" max. (5.40 x 8.57 x 0.18 cm)

Weight

0.24 oz (6.8 g)

Card Construction

ABS Shell with PVC Cover Label.

Operating Temperature

-40° to 160° F (-40° to 70° C)

Operating Humidity

5-95% non-condensing

Operating Frequency

13.56 MHz

RF Interface

ISO 15693 read/write

Transaction Time

<100 ms typical

Baud Rate

26 Kbps

Memory Type

EEPROM, read/write

Multi-application Memory

2k bit (256 Byte) card – 2 application areas

Write Endurance

Min. 100,000 cycles

Data Retention

10 years

Specifications subject to change without notice.

© 2005 HID Corporation. All trademarks and registered trademarks are property of their respective owners.

All rights reserved
Printed in the U.S.A.

LITCLAMDSUS 9/2005

www.hidcorp.com

An ASSA ABLOY Group company

9292 Jeronimo Road
Irvine, CA 92618-1905 U.S.A.
PHONE +1 (949) 598-1600 or (800) 237-7769
FAX +1 (949) 598-1690



ASSA ABLOY