


DS-2CC102P(N)-IR1(IR3) Analog IR Camera





Key Features

- Compact design
- 1/3" Sony CCD
- Minimum Illumination: 0.1Lux/F1.2 (0 Lux with IR)
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Internal synchronization
- Weather Proof: IP66 standard

Specifications

Camera

Image Sensor 1/3" Sony Super HAD CCD Signal System PAL / NTSC

Effective Pixel PAL: 500 (H) × 582 (V) NTSC: 510 (H) × 492 (V)

Min. Illumination 0.1Lux @ F1.2 (0 LUX with IR) Electronic Shutter Speed 1/50(1/60)s to 1/100,000s Lens

"-IR1" Series: 6mm
"-IR3" Series: 12mm

Horizontal Resolution 420 TVL Sync. System Internal

Video Output 1Vp-p Composite Output (75 Ω / BNC)

S/N Ratio 48 dB BLC On

General

Operating Temperature -10°C ~ 60°C Housing IP66 Standard

IR Distance "-IR1" Series: Up to 10 Meters
"-IR3" Series: Up to 30 Meters

Power Supply 12V DC Power Consumption IR1: 3W Max. IR3: 6W Max.

Dimension IR1: 76.5mm×73mm×125.5mm

IR3: 86.5mm×83mm×160mm

Weiaht IR1: 600 g

IR3: 1000 g

www.hikvision.com 53