

DS-4002/4004MDI+ Matrix Decode Card



Key Features

- High performance DSP hardware decompression
- Decoding capability: Up to 4-ch video stream at 4CIF resolution, 8-ch video stream at DCIF/2CIF resolution or 16-ch video stream at CIF resolution
- Up to 4-ch video & audio output
- Up to 4x4 multiplex windows display
- Picture-In-Picture display

Specifications

		DS-4002MDI+	DS-4004MDI+
Video/Audio output	Support Video compression Standard	H.264	
	Video Output	2-ch	4-ch
	Video Output Interface	BNC (1.0Vp-p, 75Ω)	
	Video Standard	PAL/NTSC	
	Resolution	2-ch 4CIF Or 4-ch DCIF/2CIF Or 8-ch CIF/QCIF	4-ch 4CIF or 8-ch DCIF/2CIF or 16-ch CIF/QCIF
	Frame rate	PAL: 1/16~25fps; NTSC: 1/16~30fps	
	Support Audio Compression Standard	OggVorbis	
General	Audio output	2-ch PCM, mono	4-ch, mono
	Audio output interface	BNC(Linear Level, 600Ω)	
	PCI Standard	PCI2.2	
General	Power Consumption	<10w	<16w
	Dimension	168x101mm(6.61"x3.98")	220mm*89mm(8.66"x3.50")