

## DS-4004MDI PCI Matrix Decode Board



### Key Features

- 8-ch CIF real time decoding, or 8-ch 2CIF real time decoding, or 4-ch 4CIF real time decoding, or 2-ch 4CIF with 6-ch CIF real time decoding
- 4-ch audio and video outputs
- Up to 16 multiplex windows
- Video output resolution up to 4CIF+2xQCIF

### Specifications

#### Video/Audio Output

Video Output	4
Video Output Interface	BNC, 1.0Vp-p, 75Ohm
Decoding Resolution	4CIF/2CIF/CIF/QCIF
Audio Output	4
Audio Output Interface	BNC, Linear output, 600Ω
Audio Decoding	8
Frame Rate (Per Channel)	4CIF: 25(P)/30(N)fps CIF: 25(P)/30(N)fps

#### General

Power Consumption	< 7.5W
Operating Temperature	-10°C ~ 50°C
Humidity	10% ~ 90%
Size	158mmx108mm

#### System Requirement

OS	Windows 2000/XP/2003/Vista, Redhat 9.0, Fedora 3, Fedora 4, Fedora 5, Fedora 6, Fedora 7, Fedora 8
CPU	Intel Series
Motherboard	Based on Intel 845 / 865 / 915 / 925 / 945 / 965 / Core2 / Core4 Chipset
Memory	256MB or Above
Display Adapter	Display Adapter Driver Must Support BLT. Please Refer to Hikvision Website ( <a href="http://www.hikvision.com">www.hikvision.com</a> ) for Recommended Models.