


DS-4101HDI High Definition Decode Card



Key Features

- 1-ch 1080P, or 2-ch 720P, or 4-ch 4CIF decoding
- Support DVI/VGA, HDMI, BNC, or YPbPr output interface
- Support various display resolution

Specifications

		DS-4101HDI
Video/Audio output	Video output	1-ch
	Video output interface	DVI/VGA, HDMI, CVBS(BNC) or YPbPr Interface
	Decoding resolution	HD1080(1920x1080)/UXGA(1600x1200)/SXGA(1280x1024)/720p(1280x720)/4CIF/DCIF/2CIF/VGA/QVGA/CIF/QCIF
	Video decoding	1-ch HD1080/UXGA/SXGA or 2-ch 720p or 4-ch 4CIF/DCIF/2CIF/VGA/QVGA/CIF/QCIF
	Audio output	1-ch
	Audio output interface	BNC
	Audio decoding	4-ch
General	Power consumption	< 9.5W
	Working temperature	-10°C~+50°C(14°F~122°F)
	Working humidity	10%~90%
	Dimension	133x102mm(5.24"x4.02")
System requirements	OS	Windows 2000/XP/2003/Vista/7/Linux
	CPU	Intel C4/P4/Core2/Core4 Series
	Motherboard	Based on Intel 845/865/915/925/945/965/G31/G33/P31/P35/P43/P45 Series. Please refer to the compatible list on the Hikvision website
	Memory	512MB or above
	Display Adapter	ATI Radeon X1650/X1600/X1550/X1300/X800/X600/X550/HD2400/HD2600 ATI Radeon 7000/7200/7500/8500 /9000/9200 /9500/9600 NVIDIA GeForce 8600GT/8500GT/8400GS/7600/7300LE/6600LE/6200LE Please refer to the compatible list on the Hikvision website