

DS-6101HFI-IP Digital Video Server



Key Features

- High performance DSP hardware compression
- H.264 video compression
- Dual streams
- Support variable bit rate and frame rate
- Embedded Linux OS

Specifications

Video/Audio Input

Video Compression	H.264
Video Input	1
Video Input Interface	BNC, 1.0Vp-p, 75Ω
Audio Compression	OggVorbis 16Kbps
Audio Input	1
Audio Input Interface	BNC 2.0Vp-p, 1kΩ
Intercom	1, RCA 2.0Vp-p, 1kΩ

External Interface

Network Interface	1 RJ45 10M/100M
RS-232 Port	1 RJ45 RS-232 Port
PTZ Port	Screw terminal (T+, T-)
Alarm Input	1 (Terminal Block)
Relay Output	1 (Terminal Block)

Video/Audio Output

Encode/Decode Resolution	4CIF/DCIF/2CIF/CIF/QCIF
Frame Rate	4CIF: 25(P)/30(N) fps
Dual Stream	32Kbps ~ 8Mbps
Bit Rate	Yes
Audio Output	1 (RCA Linear Electrical Level, 600Ω)

General

Power Supply	12VDC
Power Consumption	≤3W
Operating Temperature	-10°C ~ 55°C
Humidity	10%~90%
Size	70mmx120mmx45mm)
Weight	≤0.5Kg