

DS-7108HI-S Standalone DVR



Key Features

- Each channel supports up to CIF real-time encoding
- Video loop output interface
- VGA output
- 2 SATA interface
- Support main and auxiliary video output

Specifications

Video/Audio Input

Video Compression	H.264
Video Input	8 Ch
Video Input Interface	BNC (1.0Vp-p ,75Ω)
Audio Compression	OggVorbis, 16Kbps
Audio Input	4 Ch
Audio Input Interface	RCA (2Vp-p ,1KΩ)
Intercom	1 Ch (1st Ch of Audio Input)

Video/Audio Output

Display	PAL: 704x576 NTSC: 704*480
Recording Resolution	CIF/QCIF
Main Video Output	1 Ch, BNC (1.0Vp-p ,75Ω)
Aux Video Output	1 Ch, BNC (1.0Vp-p ,75Ω)
Video Loop Output	8 Ch
Recording/Playback	CIF: 25(P)/30(N)
Audio Output	1 Ch,RCA (Linear Electrical Level, 600Ω)
Dual Streams	Yes
Bit Rate	32Kbps ~ 8Mbps
VGA Output	1 (Support 800x600 (60Hz), 1024x768 (60Hz), 1280x1024 (60Hz))

Hard Disk Drive

Interface	SATA x 2
Capacity	Each HDD Supports Up to 2000GB

External Interface

Communication Interface	1 RJ45 10M/100M Ethernet Port 1 RS-232 port
RS-485 Port	1 (T+, T-, R+, R-)
USB Interface	1
Alarm Input	16 (Terminal Block)
Alarm Output	4 (Terminal Block)

General

Power Supply	12VDC
Power Consumption	≤40W (w/o HDD)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Dimensions	445mm(W)x290mm(D) 44mm(H)
Weight	≤3.28Kg (w/o HDD)