

DS-8002AHI-S ATM/POS DVR



Key Features

- Each channel supports up to CIF real-time encoding
- Dual streams
- VGA output
- 4 SATA interface
- Overlay card number, transaction type, amount and other information on video

Specifications

Video/Audio Input

Video Compression	H.264
Video Input	3
Video Input Interface	BNC (1.0Vp-p, 75Ω)
Audio Compression	OggVorbis, 16Kbps
Audio Input	3
Audio Input Interface	BNC (2.0Vp-p, 1kΩ)
Intercom	1, BNC (2.0Vp-p, 1kΩ)

Video/Audio Output

Display	PAL: 704x576 NTSC: 704x480
Recording Resolution	CIF/QCIF
Simultaneous Playback	2 Ch
Video Output	1 Ch BNC (1.0Vp-p, 75Ω) 1 Ch RCA (1.0Vp-p, 75Ω)
Recording/Playback	CIF: 25(P)/30(N) fps
Dual Stream	Yes
Bit Rate	32Kbps ~ 8Mbps
Audio Output	1 Ch BNC (Linear, 600Ω) 1 Ch RCA (Linear, 600Ω)
VGA Output	1, Support 800x600 (60Hz), 800x600 (75Hz), 1024x768 (60Hz)

Hard Disk Drive

Interface	SATA x 4
Capacity	Each HDD Supports Up to 2000GB

External Interface

Communication Interface	1 RJ45 10M/100M UTP Network port 1 RJ45 RS-232 port
RS-485 Port	1 (T+, T-, R+, R-)
USB Interface	1
Alarm Input	4 (Terminal Block)
Alarm Output	2 (Terminal Block)

General

Power Supply	100~240VAC, 6.3A, 50~60Hz
Power Consumption	≤70W (w/o HDD or DVD-R/W)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Dimensions	180mm(H)x180mm(W) x280mm(D)
Weight	≤5Kg (w/o HDD or DVD-R/W)