

## DS-8008HSI-S Standalone DVR



## Key Features

- Each channel supports up to 2CIF encoding
- Video loop output interface
- 8 SATA interface
- eSATA interface for high-speed backup (optional)

## Specifications

### Video/Audio Input

|                       |                    |
|-----------------------|--------------------|
| Video Compression     | H.264              |
| Video Input           | 8                  |
| Video Input Interface | BNC (1.0Vp-p, 75Ω) |

### Hard Disk Drive

|           |                                |
|-----------|--------------------------------|
| Interface | SATA x 8                       |
| Capacity  | Each HDD Supports Up to 2000GB |

### Video/Audio Output

|                      |                                                                    |
|----------------------|--------------------------------------------------------------------|
| Display              | PAL: 704x576<br>NTSC: 704x480                                      |
| Recording Resolution | 2CIF/CIF/QCIF                                                      |
| Video Loop Output    | 8                                                                  |
| Video Output         | 1 channel, BNC (1.0Vp-p, 75Ω)                                      |
| Recording/Playback   | 2CIF: 8fps<br>CIF: 25(P)/30(N)fps                                  |
| Bit Rate             | 32Kbps ~ 8Mbps                                                     |
| VGA Output           | 1, Support 800x600 (60Hz),<br>1024x768 (60Hz), 1280x1024<br>(60Hz) |

### External Interface

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Communication Interface | 1 RJ45 10M/100M Ethernet Port<br>1 RJ45 RS232 Port |
| RS-485 Port             | 1 Port (T+, T-, R+, R-)                            |
| Keyboard Interface      | 1 Port (D+, D-)                                    |
| USB Interface           | 1                                                  |
| Alarm Input             | 16 (Terminal Block)                                |
| Alarm Output            | 4 (Terminal Block)                                 |

### General

|                       |                               |
|-----------------------|-------------------------------|
| Power Supply          | 100~240VAC, 6.3A, 50~60Hz     |
| Power Consumption     | ≤70W (w/o HDD and DVD-R/W)    |
| Operating Temperature | -10°C ~ 55°C                  |
| Humidity              | 10% ~ 90%                     |
| Chassis               | 19" Standard                  |
| Dimensions            | 470mm(D)x441mm(W)<br>x90mm(H) |
| Weight                | ≤8Kg (w/o HDD and DVD-R/W)    |