HIKVISION

DS-D5043FL
43" Monitor

Overview

DS-D5043FL is a reliable surveillance display with LED backlit technology, excellent color reduction and image processing, truly display the video details. Multiply interfaces are able to meet various surveillance environments, and build-in speaker is convenient to audio play. DS-D5043FL is an ideal choice for security and surveillance application.

key Features

- LED backlit technology with full HD 1920 x 1080
- Wide view angle: 178°(H)/178°(V)
- Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction, Skin correction
- Multiply inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Build-in speaker
- Image freeze
- High reliable components for 7 x 24 working

Model

DS-D5043FL

Interfaces

Interfaces	Description
HDMI	HDMI Digital Signal Input
DVI IN	DVI Digital Signal Input
VGA IN	VGA Analog Signal Input
CVBS/IN	Composite Video Input
USB	USB
AUDIO IN	Audio Input
AUDIO OUT	Audio Output
RS232 IN	Serial Input

DS-D5043FL
43" Monitor

Specification

Model	DS-D5043FL
Display	
Display Type	LED-Backlit TFT LCD
Screen Size	43"
Pixel Pitch(H×V)	0.163 mm x 0.490 mm
Max Resolution	1920 x 1080
Brightness	400 cd/m² (Typical)
Contrast	1200 : 1
Response Time	8 ms
Color	16.7 M
Viewing Angle	Horizontal 178°, Vertical 178°
Input	
HDMI	HDMI x 1
VGA	VGA x 1
DVI	DVI x 1
BNC	BNC x 1
USB	USB x 1
RS232	RS232 x 1
Audio	
Audio In	1
Audio Out	1
Speaker	8 Ω 3W x 2
General	
Power Supply	AC100 ~ 240 V, 50 / 60 Hz
Consumption	< 100 W(on) < 1 W(Standby)
Operation Temperature	0°C ~ 40 °C
Operation Humidity	10%~90%
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10%~95%
Dimension (W×H×D)	996.4 mm × 590.8 mm × 48.6 mm (37.88" x 22.46" x 2.82")
Weight	28 Kg(Gross weight) , 20 Kg(Net weight)
Included Accessories	Remote control x 1, battery x 2, power cord x 1, user manual x 1, warranty card x 1, CD x 1

HIKVISION

Dimension (mm)

996.41

590.8

792.3

400

200

4-M6

452.6

21.9
48.6