

DS-KAW150-2N

- 24 VDC, 150 W output power supply for door station with LED power indicator
- Short circuit protection, over load protection, and over power voltage protection
- Natural air cooling
- 105 °C long life electrolytic capacitor
- 5 seconds 300VAC surge voltage input tolerance
- High working temperature up to 70 °C

▪ Specification

Device interfaces	
Power supply input	1, 100 VAC to 240 VAC
Power supply output	Max. 24 VDC, 6.25 A
General	
Weight	Net weight: 0.560 kg
	Gross weight: 0.646 kg
Working temperature	Operating: -10 °C to 70 °C (14 °F to 158 °F)
	Storage: -25 °C to 85 °C (-13 °F to 185 °F)
Working humidity	< 95% (no-condensing)
Cooling system	Convection
Dimension (L x W x D)	178 mm × 97 mm × 38 mm (7.01" × 3.82" × 1.50")
Power supply	100 VAC to 240 VAC
Power consumption	150 W

▪ Available Model

DS-KAW150-2N

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq