

## DS-TMC407-E All-in-One Entrance & Exit Manager

### Introduction

DS-TMC407-E is integrated with camera, supplement light, LCD (LED is optional), pickup, speaker, etc. The device adopts HD progressive scan CMOS and features in high quality imaging, low illumination, high frame rate, good color rendition, etc. It supports H.265 encoding to save storage space. It adopts advanced deep-learning algorithm to realize video detection and capture. It provides various functions, including vehicle license plate detection, vehicle without plate detection, vehicle feature detection, anti-vehicle following, etc. It is widely used in community, shopping mall, school, hospital, airport, gas station, 4S automotive dealership, government, etc. to capture and recognize the entering and exiting of vehicles.




### Key Feature

- **High definition:** 4 MP HD camera with max. 2688 × 1520 resolution and 25 fps frame rate. High quality imaging with 1/3" progressive scan CMOS. 0.022 lux low illumination with clearer imaging at night.
- **Highly integrated:** The device is integrated with camera, LCD, LED supplement light, lens, pickup, and speaker, which helps to reduce construction and wiring costs. The all-in-one structure brings simple wiring and convenient debugging.
- **LCD:** 21.5 inch LCD can show QR code for vehicles without license plates to scan to enter and exit, and it can also play image, video, and advertisement.
- **Two-way audio:** Supports pressing help button to realize real-time two-way audio with center and remote booth.
- **Supplement light:** Embedded with 9 bright LED lights, the device has smart supplement light technology, which supports supplement light control according to time and brightness.
- **Remote debugging:** 3.1 to 6 mm motor-driven varifocal lens, remote debugging is quick and easy.
- **Anti-vehicle following mode:** Supports anti-vehicle following mode via video and radar/loop. The boom pole can keep rising in vehicle queue scenario to solve the congestion.
- **Ingress protection:** The surface of the host adopts anti-UV and electrostatic spraying, and the level of dustproof and waterproof meets the requirement of IP45 for outdoor devices.



## Typical Application



## Available Model



DS-TMC407-E(LCD)

## Specification

<b>Model</b>	<b>DS-TMC407-E</b>
<b>Camera</b>	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	Color: 0.022 Lux @ (F2.0, AGC ON) B/W: 0.011 Lux @ (F2.0, AGC ON)
Shutter Speed	1/30 s to 1/100,000 s
Lens Type	3.1 to 6 mm varifocal lens, motor-driven lens
IR Cut Filter	Supported
<b>Compression Standard</b>	
Video Compression	H.264/H.265/MJPEG
Video Bit Rate	32 Kbps to 16 Mbps
<b>Image</b>	
Image Format	JPEG
Max. Image Resolution	2688 × 1520
Frame Rate	25 fps @ (2688 × 1520)
Image Settings	Saturation, brightness, contrast, white balance, AGC, and 3D noise reduction can be adjusted via the web browser.
<b>Network</b>	
Storage	Built-in TF card
Protocol	TCP/IP, HTTP, DHCP, DNS, RTP, RTSP, NTP, FTP picture upload
Network Security	Heartbeat, password protection, NTP
<b>Capture</b>	
Picture Format	JPEG with configurable quality
Smart Recognition	ANPR, vehicle type recognition, vehicle logo recognition, sub-brand recognition
<b>Supplement Light</b>	
Supplement Light Control	Control according to brightness or time
LED Light Bead Number	9
Color Temperature	3000 K
<b>Camera Interface</b>	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet interface
Serial Port	1 built-in RS-485 serial port, 1 built-in RS-232 serial port
Triggered Input	3-ch triggered/alarm inputs
Relay Output	2-ch relay outputs, supporting rising of barrier gate boom pole
<b>LCD</b>	
Dimension	21.5 inch

Resolution	1080p
Max. Brightness	1500 cd/m <sup>2</sup>
<b>General</b>	
Working Temperature	-20 °C to 70 °C (-4 °F to 158 °F)
Working Humidity	90% or less (non-condensing)
Power Supply	220 VAC
Lightening Protection	Supported
Weight	37 kg (81.6 lb)
Consumption	85 W (with LCD)

## Dimension



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com