

## accord

#### CONTACT US

Ademco Microtech								
2 Redwood Crescent								
Peel Park Campus								
East Kilbride								
G74 5PA								
Scotland								-
Sales enquiries								

Tel: +44 (0) 1355 354000 Fax: +44 (0) 1355 239542 Email: sales@ademco.co.uk

#### Technical support for existing customers:

Accord technical support

Tel: +44 (0) 1355 260796 Fax: +44 (0) 1355 267796 Email: support@ademco.co.uk

#### Other products in the Ademco Microtech range:

#### Galaxy

Incorporating the latest system technology, the Galaxy range of security control panels provides an extensive collection of solutions to every kind of security installation requirement.

#### Vista

The Vista security control system presents the security industry with a truly flexible alternative to conventional security options. Available in 10 or 25 zone with wire-free configuration options.

#### PIRs

Ademco Microtech manufactures and markets a range of digital detectors to complement all intruder alarms panels.

### See our full range on the website:

http://www.ademco-microtech.co.uk



PEACE OF MIND FOR HOME AND BUSINESS


# accord





residential





6





### reliable

It is ideal for both residential and small commercial applications with both bells only and communicating panels available.



#### ACCORD xpC WITH COMMUNICATOR

#### The Accord xpC control panel

The Accord xpCxpC adds security and peace of mind to both home and business.

The three setting options available mean that the installer can programme the system to set in the following ways:

- FULL Set when the property is empty
- PART Set when the property is occupied
- C NIGHT Set when going to bed.

#### **Features**

- 8 fully supervised programmable zones
- Programmable zone function per area set
- Built-in communicator
- Built-in software modem for up/downloading
- 10 different zone types including fire
- Choice of LED and Icon Keypads
- Up to 4 stylish remote keypads with backlit keys
- Built-in panic attack facility
- 8 user codes
- 3 setting options of:
  - FULL Set
  - PART Set
  - NIGHT Set
- Selection of wiring options include: Normally closed loops Supervised double pole USA End Of Line
- Technistore remote reset for all 256 versions
- Duress code options
- Easy set option
- Full 250 time and date stamped event log
- Event log printer option
- Space for 7Ah Battery

#### The new Accord Icon keypad

Exclusive to the versatile xpC control panel, this stylish keypad offers the end-user a simple, easy to follow setting procedure.

Setting the system is as simple as entering a personal security code and then:

- FULL Set
- PART Set
- ( NIGHT Set

Unsetting the system is achieved by simply entering the personal security code.



xpC control panel

dimensions: 300mm x 250mm

#### Part Numbers

Accord xpC control panel	2011-123
Accord xpC LED Keypad	2011-124
Accord xpC Icon Keypad	2011-129
Accord xpC LED Kit (xpC panel c/w LED Keypad)	2011-131
Accord xpC Icon Kit (xpC panel c/w Icon Keypad)	2011-132

#### Technical data

Mains supply	230v AC 50Hz nominal
Power Supply	12v DC 750 mA
Bell Output	12v DC 500 mA
Strobe Output	12v DC 250 mA
Internal speaker driver	16 Ohms



Icon keypad dimensions: 135mm x 70 mm

### accord



#### ACCORD 8 ZONE CONTROL PANEL

#### The Accord control panel

The Accord panel offers a simple to install, competitively priced bells only system for residential applications.

#### Features

- 8 fully programmable zones with a common tamper
- Programmable zone function per area set
- Up to 4 stylish LED remote keypad's with backlit keys
- Built-in keypad panic facility
- 16 event alarm memory
- 8 user codes
- 7 different zone types including fire
- 3 setting options:
  - FULL Set
  - PART Set
  - NIGHT Set
- Engineer reset facility
- Easy set option
- Programmable trigger output
- User test facility
- SAB Bell output
- Space for 7AH Battery



196mm x 285mm

#### Part Numbers

Accord control panel with LED keypad	2011-107
Accord LED keypad	2011-108

accord

#### Technical data

Mains supply	230v AC 50Hz nominal
Power Supply	12v DC 750 mA
Bell Output	12v 500 mA
Strobe Output	12v 250 mA
Internal speaker driver	16 Ohms



LED keypad dimensions: 119mm x 119mm